

## A

Absorption of sound, *see* Sound absorption

ACGIH, *see* American Conference of Governmental Industrial Hygienists

Acoustical data, 43

Acoustical efficiency (throttling valves), 647–649

Acoustical enclosures, 521–552. *See also* Small enclosures, sound in

close-fitting, sealed, 531–537

for cooling towers, 667

defined, 517

for feed pumps, 672

for industrial gas turbines, 673

intermediate-size, 537–538

large, with interior sound-absorbing treatment, 540–551

effect of sound-absorbing treatment, 547, 548

flanking transmission through floor, 549, 550

inside-outside vs. outside-inside transmission, 549–550

key parameters influencing insertion loss, 544–545

leaks, 547, 548

machine position, 549

machine vibration pattern, 549

model for insertion loss at high frequencies, 541–544

wall panel parameters, 545–547

large, without internal sound-absorbing treatment, 538–540

partial, 551–552

performance of:

insertion loss as measure for, 522–523

measures for, 518–519

qualitative description, 523–525

size of, 521

small, sealed, 525–531

for transformers, 679

Acoustical engineers, 345

Acoustical impedance, 40

Acoustically induced vibrations and rattles, 905, 907

Acoustical modal response, 149–151

Acoustical privacy, 203–204. *See also* Speech privacy

Acoustical standards, *see* Standards

Acoustical terminology, 911

Acoustical wave equation, 149

Active machinery isolation, 840–845

Active noise and vibration control (ANVC), 721–849

actuators:

locations of, 806–808

number of, 804–806

placement and selection of, 722–730

sizing of, 808–809

controller architecture and performance simulations, 814–817

control sensors/architectures, 730–732

design considerations, 800–801

digital filters, 740–751

adaptive design for, 749–751

advantages of, 740–741

description of, 741–747

optimal design for, 747–749

feedback control systems, 779–800

alternate suboptimum control filter estimation, 784–800

basic architecture, 779–781

optimal control filter estimation, 781–784

feedforward control systems, 751–779

adaptive control, 760–765

basic architecture, 751–754

control of aliasing effects, 765–769

extension to MIMO systems, 777–779

optimal control filter estimation, 754–760

system identification, 769–777

hardware selection, 817–827

identifying performance goals for, 801–804

implementation and testing of, 827–829

performance expectations, 732–733

placement and selection of control sources/actuators, 722–730

prototype ANVC systems, 733–740

active machinery isolation, 840–845

airborne noise in high-speed patrol craft, 845–849

MIMO feedforward active locomotive exhaust with passive component, 829–840

sensors:

control sensors/architectures, 730–732

number/location of, 809–814

performance of, 813–814

reference, 809, 812–813

residual, 809–812

Active noise control silencers, 280

Actuators (ANVC):

locations of, 806–808

number of, 804–806

placement and selection of, 722–730

sizing of, 808–809

Actuator channels, 806

Adaptive control algorithm, 760–765

A/D converters, *see* Analog-to-digital converters

Added mass, 348, 355, 383–384

Added mass coefficient, 348

Added mass/fluid density, 348

Added volume, 348, 355

Admittance, 41

Aeroacoustical sources, 611–616

aerodynamic dipoles, 612–613

aerodynamic monopoles, 611–612

aerodynamic quadrupoles, 613–614

of fractional orders, 614

influence of source motion, 615–616

Aerodynamic dipoles, 612–614

Aerodynamic monopoles, 611–612, 614

Aerodynamic sound, 611, 643–656. *See also* Gas flow noise

AFOSHSTD (Air Force Occupational, Safety, and Health Standard), 881

AI, *see* Articulation index

Air bag deployment noise, 869

- Airborne excitation, simultaneous dynamic excitation and, 462–465
- Airborne sound (noise):
  - in high-speed patrol craft, 845–849
  - outdoors, 121
- Airborne whole-body vibration criteria, 881
- Air compressors, predicting noise from, 660–662
- Air-Conditioning and Refrigeration Institute (ARI), 911
- Air-cooled condensers, predicting noise from, 667–668
- Aircraft interior noise control, 736
- Airflow velocity (HVAC systems), 701–703
  - fans, 707
  - near grilles, 701–702
  - terminal boxes/valves, 708–709
- Airfoils:
  - "singing" of, 640
  - sound generation by, 639–640
- Air Force Occupational, Safety, and Health Standard (AFOSHSTD), 881
- Air mounts, 739
- Air Movement and Control Association (AMCA), 670
- Air pressure ratios, 648
- Air spring isolators, 577
- Aliasing, 817
  - active control of, 765–769
  - in spectral analysis, 54
- All zero filters, 743
- Almost periodic signals, 44
- AMCA (Air Movement and Control Association), 670
- American Conference of Governmental Industrial Hygienists (ACGIH), 871, 881, 882
- American National Standards Institute (ANSI), 878, 911
- American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE), 706, 711, 911
- American Society of Mechanical Engineers (ASME), 911
- American Society of Testing and Materials (ASTM), 911
- American system of units, 935–937
- Amplification, 583
- Amplification at resonance, 583
- Analog-to-digital (A/D) converters, 741–742, 766, 767
  - for ANVC systems, 819–825
  - sampling process of, 817
- Anechoic spaces/rooms, 82, 97–98, 211
- ANSI, *see* American National Standards Institute
- Antialiasing filters, 54, 57, 765–769
  - and ANVC performance, 815
  - selection of, 817–819
- ANVC, *see* Active noise and vibration control
- Applications Handbook* (ASHRAE), 711
- Architectural acoustics, standards for, 930–931
- Architectural noise control in buildings, standards for, 926–931
- Area sources, 122
- ARI (Air-Conditioning and Refrigeration Institute), 911
- ARMA filters, 744
- Armed forces sound exposure criteria, 863, 867–868, 874
- Articulation index (AI), 203–204
- ASHRAE, *see* American Society of Heating, Refrigerating, and Air-Conditioning Engineers
- ASHRAE handbooks, 706, 711
- ASME (American Society of Mechanical Engineers), 911
- ASTM (American Society of Testing and Materials), 911
- Asymptotic threshold shift (ATS), 865, 866
- Atmospheric absorption, 136
- ATS, *see* Asymptotic threshold shift
- Audio engineers, 345
- Audio frequency region, 859–867, 873
- Auralization, 190
- Autocorrelation function, 60
- Automotive interior noise control system, 735–736
- Autoregressive moving average filters, 744
- Autospectral density functions, 55–59
- Averages:
  - linear, 48
  - running, 49–50
  - synchronous averaging, 51–52
  - unweighted, 48, 49
  - weighted, 48–49
- Average A-weighted sound level, 17
- Average diffuse-field surface absorption coefficient, 184–185
- Average sound level, 16
- A-weighted equivalent sound level, 887
- A-weighted sound level, 888–891
- A-weighted sound (noise) exposure level, 18, 858, 859
  - coal car shakers, 664
  - diesel-engine-powered equipment, 668
  - transformers, 677–678
- A-weighted sound power level, 73–75
  - air compressors, 661
  - in diffuse field, 81
  - estimates of, 659
  - feed pumps, 673
  - steam turbines, 676
  - wind turbines, 680
- A-weighted sound pressure level, 15–16
  - long-term, 139
  - for noise exposure, 858, 859
  - for outdoor sound, 121
  - overall, 142–143
- B
- Background noise:
  - in classrooms, 196–197
  - for speech intelligibility, 192–193
- Backward-traveling plane wave, 32
- Baffled pistons, sound power output of, 35, 36
- Balanced noise criterion (NCB) curves, 894, 895
- Bandwidths:
  - of continuous-spectrum sound, 7–9
  - conversion of, 10–11
  - half-power, 165
  - with tapering, 57
- Barriers, 132

- cooling towers, 667
- effectiveness of, 345
- for open-plan offices, 202–203
- for outdoor sound, 120, 132–135
  - close to trees, with gaps and slots, 138–139
  - interaction of ground and, 137–138
  - and uncertainty of attenuation, 141–142
- with transformers, 679
- Beams:
  - damping due to reinforcements, 591–592
  - infinite:
    - effective length connecting force and moment impedance, 502
    - transmission through, 395–397
  - power transmission to plate from, 410–413
  - viscoelastic damping of:
    - three-component beams, 602–606
    - two-component beams, 599–600
- Beam-tracing techniques, 189–190
- Bels, 12, 75
- BEM (boundary element model), 121
- Bending waves:
  - complete power transmission for, 412–413
  - reflection loss of, 407–410
    - in beams, 411–412
    - and change in cross-sectional area, 407
    - free bending waves at  $L$ -junctions, 408
    - in plates with vibration break, 415–416
    - through cross junctions and T-junctions, 409–410
  - through infinite plates, 417–418
- Bias error, 59
  - in coherent output power calculations, 65
  - in gain factor estimates, 62
  - in intensity measurement, 105, 106
- Blocked pressure, 626, 629
- Block's formula for shallow cavities, 641–642
- Boilers, predicting noise from, 662–663
- Boundaries, damping due to, 591
- Boundary conditions, 150, 151, 159
- Boundary element method, 156
- Boundary element model (BEM), 121
- Breakin noise, HVAC, 703–705
- Breakin sound transmission loss, 450–451
- Breakout noise, HVAC, 703–705
- Breakout sound transmission loss, 448–450
- Broadband disturbance control, 756–760
- Broadband regulation filter, 790–795, 797
- BT product, 56
- Bucket ladder unloaders, 664
- Building Bulletin 93, 193
- Butterworth filters, 817–818
- C
- Cabins:
  - acoustical performance measures of, 520
  - defined, 517
- Cauer filters, 817–818
- Cavities, flows past, 640–643
- Ceilings, for mechanical rooms, 710
- Central-processing units (CPUs), 825, 827
- CHABA, *see* National Academy of Sciences--National Research Council, Committee on Hearing, Bioacoustics and Biomechanics
- Characteristic resistance, 40
- Choked jets, 621
- Circular effects (with FFT), 50
- Clamshell bucket unloaders, 664
- Classrooms, 191–197
  - controlling sound in, 196–197
  - predicting acoustical quality of, 193–196
  - speech intelligibility in, 192–193
- Closed-loop system identification, 771–776, 827, 828
- Closed offices, sound pressure levels in, 190–191
- Closed-fitting enclosures:
  - defined, 522
  - sealed, 531–537
    - free standing, 531–534
    - machine-mounted, 535–537
  - wrappings vs., 552
- Coal car shakers, 663–664
- Coal crushers, 665
- Coal-handling equipment:
  - diesel-powered, 668
  - predicting noise from, 663–665
- Coal mills and pulverizers, 665
- Coal transfer towers, 665
- Coefficient of variation, 50
- Coherence functions (coherency squared), 58–59
- Coherent output power relationship, 64–65
- Coil spring isolators, 576
- Combination mufflers, 335–338
- Combustion noise (gas turbine engine s), 624–626
- Comparison method (sound power output), 81, 88–89
- Compensation filter (feedback control), 792–800
- Compensator-regulator architecture (feedback control), 784–785
- Complex admittance, 41
- Complex impedance, 38–40, 588
- Complex sound spectra, 12
- Composite partitions, sound transmission through, 451
- Composite structures (statistical energy analysis), 456
- Composite transmission factor, 461, 462
- Comprehensive models (noise prediction), 198
- Compression waves, 6, 390–391
  - and change in cross-sectional area, 407
  - in plates with vibration break, 414–415
- Compressive force, 347–348
- Concentric-tube resonator (CTR), 304–311
- Concurrent system identification, 771
- Conference rooms, 191
- Construction equipment, diesel-powered, 668
- Continuity equation, 27
- Continuous spectra, 2–3, 7–11

Control authority (ANVC), 730

Conversion factors, 939–942

Cooley-Tukey algorithm, 53–54

Cooling towers, predicting noise from, 666–667

Core noise, 624–625, 679

Correlation coefficient function, 60–61

Correlation functions, 60–61

Cosine-squared taper, 55, 57

Coulomb damping, 588

Coupling loss factor, 456

CPUs, *see* Central-processing units

Critical bands, 900

Critical damping coefficient, 559, 581

Critical damping ratio, 162

Cross-correlation function, 67–69

Cross junctions, reflection loss of bending waves through, 409 – 410

Cross-sectional area:

- of HVAC ducts, 687, 691
- power transmission and change in, 406–407

Cross-spectral density (CSD) matrix, 804–808, 810–814

Cross-spectral density functions, 57–59

CSD matrix, *see* Cross-spectral density matrix

CTR, *see* Concentric-tube resonator

Current-day sound-level meters, 888

Cylindrical array (microphones), 93, 94, 96

Cylindrical sound sources, 4

**D**

D/A converters, *see* Digital-to-analog converters

Damage risk criteria:

- for hearing, 858–874
  - impulse noise, 867–869
  - infrasound exposure, 869, 870
  - noise exposure criteria for audio frequency region, 861 – 867
  - protection of, 871–874
  - ultrasound exposure, 869–871
- human vibration response, 874–883
  - exposure guidelines, 877–883
  - hand-transmitted vibration effects, 877
  - whole-body vibration effects, 875–877

Damping, 174–176

- critical damping ratio, 162
- effect of, 561
- in HVAC ducts, 701, 703
- structural, 561, 579–607
  - analytical models of, 588
  - due to boundaries and reinforcements, 591–592
  - due to energy transport, 592–594
  - effects of, 579–580
  - energy dissipation and conversion, 589–590
  - measurement of, 586–588
  - measures of, 580–586
  - models of, 588–589
  - viscoelastic, 594–607
    - in two-stage isolation systems, 573, 574
    - viscous, 561

Damping capacity, 584

Damping ratio, 559, 561, 581

Dashpots, 395

- in mass-spring-dashpot system, 557–560
- point force impedance for, 394

Data analysis, 43–69

- analog, 52
- applications, 61
- correlation functions, 60–61
- deterministic data, 44–45
- mean-square values, 47–48
- mean values, 47
- for periodic excitation source identification, 63–64
- for propagation path identification, 66–69
- random data, 45–47
- for random excitation source identification, 64–66
- running averages, 49–50
- spectral functions, 52–59
  - auto (power) spectral density functions, 55–58
  - coherence functions, 58–59
  - FFT algorithm, 52–54
  - line and Fourier spectral functions, 54–55
- statistical sampling errors, 50–51, 59
- synchronous averaging, 51–52
- for system response properties identification, 62–63
- types of data signals, 43
- weighted averages, 48–49

Data signals, 43

- deterministic, 44–45
- random, 45–47

Day-night sound (noise) level, 17, 888, 907

dB, *see* Decibels

Decay, *see* Sound decay

Decay distance, 603

Decay rates, 582, 587

Decibels (dB):

- fractions of, 24
- and reference quantities, 12
- for sound power expression, 75
- and sound pressure level, 15, 17

Deflection, 599

Deformation of solids, 492

Department of Defense (DOD), 907

Deterministic data signals, 44–45

- spectral computations for, 55
- statistical sampling errors with, 59

DI, *see* Directivity index

Diesel-engine-powered equipment, predicting noise from, 668–669

Diffuse-field theory, 184–187

Diffuse (reverberant) field, 76–77

- control of, 200–201
- driving freely hung panel, 457–459
- measurement in, 82