

## A

- ABS, *see* Acrylonitrile/butadiene/styrene polymers; American Bureau of Ships
- Acetals, 359–360
- ACIS (American Committee for Interoperable Systems), 713
- Acoustic enclosures, 1244–1245
- Acrylonitrile/butadiene/styrene polymers (ABS), 344, 345
- Acrylonitrile/styrene/acrylate (ASA) polymers, 345, 346
- Adhesives, 805–806, 810
- Adversaries, project, 586
- Advocates, project, 586
- Aerospace Materials Specifications (AMS), 27
- Affinity diagram, 991
- Algorithm for problem solving, *see* ARIZ
- Alkyd resins, 374
- Allowable unit stress, 498
- Alloys
  - aluminum, *see* Aluminum alloys
  - copper, *see* Copper alloys
  - magnesium, *see* Magnesium alloys
  - nickel, *see* Nickel alloys
  - shape memory, 428–429
  - super-, *see* Superalloys
  - titanium, *see* Titanium alloys
- Alloy Center, 460–461
- Alloy elements, microstructure/properties of, 233, 234
- Alloy steel(s), 29–37
  - aluminum in, 23
  - boron in, 23–24
  - calcium in, 24
  - carbon in, 19–21
  - chromium in, 22
  - copper in, 22
  - dual-phase steels, 31
  - elements used in, 18–24
  - heat-resistant steels, 35–36
  - higher alloy steels, 31–37
    - heat-resistant steels, 35–36
    - stainless steels, 31–35
    - tool steels, 35
    - ultrahigh-strength steel, 36–37
    - wear-resistant steels, 36
  - high-performance steels, 31
  - hydrogen in, 24
  - lead in, 24
  - low-alloy steels, 29–31
  - manganese in, 20, 22
  - microalloyed steels, 30
  - molybdenum in, 22
  - nickel in, 22
  - niobium in, 23
  - nitrogen in, 24
  - phosphorus in, 21–22
  - rare earth elements in, 24
  - residual elements in, 24
  - selenium in, 24
  - silicon in, 21
  - stainless steels, 31–35
    - austenitic, 19, 32–33
    - duplex, 34
    - ferritic, 3, 32–33
    - martensitic, 34
    - precipitation hardening, 35
  - sulfur in, 22
  - tantalum in, 23
  - titanium in, 23
  - tool steels, 35
  - trip steels, 31
  - tungsten in, 23
  - ultrahigh-strength steels, 36–37
  - vanadium in, 22–23
  - wear-resistant steels, 36
  - zirconium in, 24
- Alpha alloys (titanium), 237, 238
- Alpha-beta alloys (titanium), 238–239
- Alpha iron, 6
- Altschuller's Levels of Inventiveness, 614–615
- Alumina-based fibers (as composite reinforcement), 389
- Aluminum, in steel, 23
- Aluminum alloys, 59–114
  - advantages of, 60–62
    - cast aluminum alloys, 62
    - wrought aluminum alloys, 60–61
  - by alloy class, 92–111
    - cast alloys, 106–111
    - wrought alloys, 92–107
  - applications of, 92–113
    - by alloy class, 92–111
    - by market area, 111–113
  - cast alloys, 106–111
    - advantages, 62
    - limitations, 63
    - mechanical properties, 78–85
  - corrosion behavior of, 86–88
    - galvanic corrosion, 87–88
    - general corrosion, 86–87
    - pitting corrosion, 87
  - designation systems for, 63–70
    - cast, 65, 67–70
    - tempered, 68, 70
    - wrought, 64–67
  - finishing of, 90–92
    - applied coatings, 91–92
    - chemical finishes, 90
    - clear anodizing, 91
    - color anodizing, 91
    - electrochemical finishes, 90
    - electrolytically deposited coloring, 91
    - electroplating, 91
    - hard anodizing, 91
    - integral color anodizing, 91
    - mechanical finishes, 90

- limitations of wrought/cast, 62–63
- machining of, 88–90
  - multipoint tool operations, 89–90
  - single-point tool operations, 88–89
- market-area applications, 111–113
  - aircraft and aerospace, 112
  - automotive, 112
  - building and construction markets, 111
  - electrical markets, 111
  - marine transportation, 112–113
  - in packaging, 113
  - petroleum and chemical industry components, 113
  - rail transportation, 113
  - specialty products, 113
- mechanical properties of, 71–85
  - castings, 78–85
  - wrought, 71–77
- nature of, 59–60
- wrought alloys, 92–107
  - advantages of, 60–61
  - limitations, 63
  - mechanical properties, 71–77
- Aluminum bronzes, 144
- American Bureau of Ships (ABS), 27
- American Committee for Interoperable Systems (ACIS), 713
- American Railway Engineering and Maintenance of Way Association (AREMA), 27
- Amino resins, 375
- AMS (Aerospace Materials Specifications), 27
- Annealing, 25
- Anode, 47
- Anodic coatings, 285
- Anthropometry, 765–767
  - data and use, 766
  - in design, 766–767
- Antimony, 24
- AOD, *see* Argon-oxygen decarburization
- Application software, 691
- Aramid fibers (as composite reinforcement), 389
- AREMA (American Railway Engineering and Maintenance of Way Association), 27
- Argon-oxygen decarburization (AOD), 4, 47–49, 317–319
- ARIZ (algorithm for problem solving), 635–639
  - caution, 639
  - flowchart, 636
  - model of ideal solution step, 638–639
  - problem analysis step, 637
  - resource analysis step, 637–638
- Aromatic polyamides, 358, 359
- Aromatic polyketones, 369, 370
- Arsenic, 24
- ASA (acrylonitrile/styrene/acrylate) polymers, 345, 346
- Ashby's method (materials selection), 471–472
- ASM International, 460–461
- ASTM E140, 16
- Austenite, 18
- Austenitic alloys
  - nickel, 40
  - stainless steels, 19, 32–33
  - welding of, 55–56
- Automated drafting, 654
- Automotive engines, ceramic wear components, 439–440
- Axial stress, 493
- B**
- Bainite, 13, 15, 25
- Ball bearings, 1103, 1106, 1108, 1109, 1112–1117
  - contact angle of, 1113–1115
  - curvature sum and difference of, 1116–1117
  - geometry of, 1112–1117
  - race conformity of, 1112, 1113
  - selection of, 1032–1035
  - shoulder height of, 1115
- Baron fibers (as composite reinforcement), 389
- Bars, steel, 5
- BASIC, 699
- Basic oxygen furnace (BOF), 4, 824–827
- Beams, stresses on, 510–530
  - continuous beams, 522–525
  - curved beams, 524–527
  - and design, 520–523
  - flexure, 510–520
    - bending moment, 515
    - equilibrium conditions, 511–512
  - impact stresses, 527–530
    - axial impacts, 528–529
    - live loads, 528
    - rupture from impact, 529–530
    - sudden loads, 527–528
  - vibratory stresses, steady/impulsive, 530
- Bearings
  - ball, 1103, 1106, 1108, 1109, 1112–1117
  - in ceramic wear applications, 438, 439
  - gas-lubricated, 1068–1091
    - journal bearings, 1069–1084
    - thrust bearings, 1075–1091
  - hydrostatic, 1060–1069
    - compensating elements of, 1066–1069
    - pad coefficients, 1062–1066
    - liquid-lubricated journal, 1044–1051
    - liquid-lubricated thrust, 1050–1061
    - and lubrication, 1032–1035
- Benchmarking, 988
- Bending, 535–536
- Bending moment, 515
- Bend tests, 973–974
- Beta alloys (titanium), 239
- Binary phase diagrams, 6
- Biological corrosion, 919
- Biomechanics (ergonomics), 769–773
  - joint movements, 769–771
  - muscle forces, 771–772

- tissue tolerances, 771–772
- BOF, *see* Basic oxygen furnace
- Bond-testers, 1276
- Boring (copper alloys), 194, 200
- Boron, 23–24
- Boundary film
  - formation of, 1149–1152
  - physical properties of, 1151–1153
  - thickness of, 1153–1155
- Boundary lubrication, 1148–1157
  - effect of operating variables, 1154–1156
  - extreme-pressure lubricants, 1156–1157
  - film thickness, 1153–1155
  - formation of films, 1149–1152
  - physical properties of films, 1151–1153
  - regime, 1040–1041
- Brake systems, 1018
- Brass(es), 44, 119, 130
  - envirobrasses, 141
  - free-cutting, 197, 198, 203
  - high strength yellow brasses, 140
  - leaded brasses, 131
  - leaded red brasses, 138
  - leaded semired brasses, 139
  - red brasses, 138
  - semired brasses, 139
  - silicon brasses, 134, 140
  - tin brasses, 132
  - yellow brasses, 139
- Brazing, 134, 202
- Breaking strength, 495
- Bridge network, 1009–1010
- Brinelling failure, 863
- Brittle-coating method, 936
- Brittle fracture, 863
- Brittle materials, 962–976
  - confidence limits for, 968, 976
  - environmentally enhanced fracture in, 966–968
    - constant-loading-rate experiments, 967–968
    - inert strength for indented specimens, 968
  - general considerations for, 963–964
  - lifetime prediction for, 963, 968–970
    - calculation, 968
    - confidence limits, 968
    - process, 969–970
  - reliability of, 962–963
  - strength/dynamic fatigue tests of, 972–975
    - bend tests, 973–974
    - best practices, 975
    - dangers, 975
    - dynamic fatigue measurements, 974, 975
    - indented inert strength, 975
    - standard flaws, 974
  - strength of, 964–966
    - minimum strength overload proof test, 965
    - nondestructive flaw detection, 965–966
    - statistical strength distribution, 964–965
    - Weibull tests of, 970–972
- Brittleness, 496
- Bronzes, 119
  - aluminium, 144
  - high-leaded tin bronzes, 143
  - leaded phosphor bronzes, 133
  - leaded tin bronzes, 142
  - nickel-tin bronzes, 143
  - phosphor bronzes, 133
  - silicon bronzes, 134, 140
  - tin bronzes, 142
- Brush seals, 1192–1198
  - brush seal flow modeling, 1197
  - brush seal materials, 1197–1198
  - design considerations for, 1193–1195
  - leakage performance comparisons, 1195–1197
- Buckling, 716

C

- CAB (cellulose acetate butyrate), 351
- CA (cellulose acetate), 351
- Cache memory, 670–671
- CAD, *see* Computer-aided design
- Cantilever beam, 510
- Carbon and carbon composites (CCCs)
  - mechanical properties of, 404–405
  - physical properties of, 414
- Carbon fibers (as composite reinforcement), 388
- Carbon matrix materials, 393
- Carbon steels, 27–29, 53–55
- Cast alloys
  - aluminum, 62, 63, 65, 67–70, 78–85, 106–111
  - copper, 138–146
  - manganese bronze, 140
  - titanium, 240, 245–247
- Casting(s)
  - continuous, 4–5
  - copper alloys, 199–201
  - mechanical properties of, 281, 282
  - with superalloys, 316–321
    - AOD, 317–319
    - component production, 321–322
    - considerations, 320–321
    - remelted ingot processing, 320
    - VIM, 318–320
  - titanium alloys, 250–251
- Cast leaded manganese bronze alloys, 140
- Cast special alloys, 146
- Cast superalloys
  - compositions of, 296–297
  - dynamic moduli of elasticity for, 310
  - effect of temperature on, 300–301
  - physical properties of, 308
- Catalysts, smart, 428
- Cathode, 47

CAVEvis, 744  
Cavitation, 919  
CCCs, *see* Carbon and carbon composites  
CCCT (critical crevice corrosion temperature), 46  
C (computer language), 699–700  
C++ (computer language), 700  
Cellulose acetate butyrate (CAB), 351  
Cellulose acetate (CA), 351  
Cellulose proprionate (CP), 351  
Cellulosic polymers, 351  
Cementite, 9, 14, 20, 25  
Central Processing Unit (CPU), 648, 662–663  
Ceramic failure, 942–961  
    delayed, 947–948  
    and design applying multiaxial Weibull statistics, 953–956  
        global multiaxial fracture criterion, 953  
        local multiaxial criterion, 954–956  
        strength under compression loading, 953  
    flaws, 944  
    fracture mechanics, 944–946  
    at high temperatures, 958–961  
        creep rupture, 960  
        creep strain, 959–960  
    scatter, 948–952  
        of lifetime, 951–952  
        of strength, 948–952  
    strength, 945–947  
    thermal shock, 957–958  
Ceramic materials, 433–449  
    brittleness of, 435–437  
    for corrosion resistance, 442–443  
    for electronic packaging materials, 804–805  
    future trends in, 448–449  
    information sources about, 446–448  
    in passive electronics, 442–444  
    piezoceramics, 444–445  
    processing of advanced, 434–435  
    standards and test methods, 446–448  
    thermostructural applications, 440–442  
    transparent, 445, 446  
    in wear applications, 437–440  
Ceramic matrix composites (CMCs)  
    mechanical properties of, 402–404  
    physical properties of, 414  
Ceramic matrix materials, 393  
Cerium, 24  
CFD, *see* Computational Fluid Dynamics (CFD)  
Chemical engineering, virtual reality applied to, 754–757  
Chemical failure, 931, 932  
Chemical finishes (aluminum alloys), 90  
Chemical method, 936–937  
Chemical resistance  
    in electronic packaging materials, 785  
    of plastics, 337  
Chromium, 22, 40, 268  
CISC (complex instruction set computer), 663–664  
CISC/RISC (complex instruction set computer/reduced instruction set computer), 663–664  
Civil engineering, virtual reality applications in, 752–755  
CMCs, *see* Ceramic matrix composites  
CNC machining, 728–730  
Coke, 4  
Cold cracking, 54–55  
Columns  
    defined, 536  
    eccentric loads on, 539  
    stresses on, 536–543  
        steel columns, 542–543  
        theory, 537–539  
        wooden columns, 539–542  
Combined stresses, 502–506  
Comparing/ranking (as method of materials selection), 452, 473–476  
    digital logic, 474–476  
    performance index, 475–476  
    weighted-properties, 474–476  
Complex instruction set computer (CISC), 663–664  
Component mounting, 806–808  
    discrete components, 806, 807  
    printed circuit board components, 807–808  
Composite materials (composites), 380–414  
    classes/characteristics of, 381–382  
    comparative properties of, 382–386  
    manufacturing considerations for, 385–386  
    matrix, 386, 390–393  
        carbon, 393  
        ceramic, 393  
        metal, 393  
        polymer, 390, 392–393  
        properties of, 391  
    mechanical properties of, 396–405  
        carbon/carbon composites, 404–405  
        ceramic matrix composites, 402–404  
        metal matrix composites, 400–402  
        polymer matrix composites, 396–400  
    physical properties of, 393–396, 405–414  
        carbon/carbon composites, 414  
        ceramic matrix composites, 414  
        metal matrix composites, 413–414  
        polymer matrix composites, 408, 409, 411, 412  
    reinforcement, 386–390  
        alumina-based fibers, 389  
        aramid fibers, 389  
        baron fibers, 389  
        carbon fibers, 388  
        fiber, 387, 388  
        glass fibers, 388  
        high-density polyethylene fibers, 389–390  
        silicon-carbide based fibers, 389  
Composite panel, 1243–1244  
Compressive strain, 493  
Compressive stress (compression), 492

- Compressor systems, 1019
- Computational Fluid Dynamics (CFD), 743–746
  - CAVEvis, 744
  - NASA Virtual Wind Tunnel, 743–744
  - ViSTA FlowLib, 744–746
  - VR-CFD, 744–745
- Computed tomography (CT), 1266–1267
- Computers, 656–701
  - and CISC/RISC, 663–664
  - classes of, 658–659
  - CPU, 656–657, 662–663
  - evolution of, 659–661
  - input devices, 678–686
    - digitizer, 683–685
    - keyboard, 678–679
    - light pen, 682–683
    - mouse, 681–682
    - scanner, 685–686
    - touch pad, 679–680
    - touch screen, 680–681
    - trackball, 682
    - TrackPoint, 682
  - input/output (I/O), 656, 657
  - mainframe, 661–662
  - memory systems, 667–678
    - external memory, 671–678
    - internal memory, 670–671
    - nonvolatile, 668
    - organizational methods, 669–670
    - PROM, 669
    - RAM, 668–669
    - ROM, 669
    - volatile, 668
  - micro-computers, 662
  - mini-computers, 662
  - networked, 662
  - output devices, 686–691
    - electronic displays, 686–688
    - hard-copy devices, 689–691
  - parallel-processing, 666–667
  - PCs, 664–665
  - software for, 691–701
    - computer languages, 697–701
    - GUI, 694–695
    - operating systems, 692–694
    - X Window System, 695–697
  - super-computers, 661
  - and word length, 662
  - workstations, 665–666
- Computer-aided design (CAD), 642–655, 701–722. *See also*
  - Standard for the Exchange of Products
  - applications of, 717
    - optimization, 718–719
    - rapid prototyping, 720–722
    - stereolithography, 721–722
    - virtual prototyping, 719–720
  - and computer-aided manufacturing, 722
  - design applications for, 647–655
    - automated drafting, 654
    - documentation, 654
    - dynamic analysis, 653, 654
    - experimental analysis, 654
    - finite-element analysis (FEA), 652–653
    - hybrid solid modeling, 651
    - kinematic analysis and synthesis, 653
    - solid modeling, 651
    - static analysis, 653
    - surface modeling, 650
    - wireframe modeling, 649
  - and design process, 645–647
  - geometric definition, 702–703
  - hardware used in, 655
  - historical perspective on, 643–644
  - software for, 701–712
    - graphics software, 701–703
    - solid modeling, 703–712
  - standards for and translators of, 712–717
    - ACIS (American Committee for Interoperable Systems), 713
    - analysis software, 713–714
    - buckling, 716
    - DFX (Drawing Exchange Format), 713
    - dynamic response, 717
    - IGES (Initial Graphics Exchange Specification), 712–713
    - linear statics, 716
    - nonlinear statics, 716–717
    - normal modes, 716
    - STEP (Standard for the Exchange of Products), 713
    - transformations, 708–711
- Computer-aided manufacturing (CAM), 651, 722
- Computerized materials databases, 485–486
- Computer languages, 697–701
- Concatenation, 710
- Conceptual design
  - and virtual reality (VR), 739–742
    - 3DM, 740
    - 3-Draw, 739
    - COVIRDS (Conceptual VIRTUAL Design System), 740, 741
    - HoloSketch, 740
    - JDCAD, 740
    - virtual sculpting, 741–742
- Conceptual VIRTUAL Design System (COVIRDS), 740, 741
- Condensation polymers, *see* Engineering thermoplastics
- Conduction, 815–816
- Confidence limits (brittle materials), 968, 976
- Conformal surfaces, 1030–1032
- Constant-loading-rate experiments, 967–968
- Constrained beam, 510
- Constrained optimization methods, 839–843
  - direct search, 839–841
  - linearization, 841–842
  - SQP (Successive Quadratic Programming), 843

- transformation, 841
- Construction, virtual reality applications in, 752–755
- Constructive solid geometry (CSG), 705–706
- Contact stress(es), 551, 552, 1086, 1087, 1089–1096
- Contact stress theory, 551
- Continuous beams, 510, 522–525
- Continuous casting, 4–5
- Continuous-cooling transformation (CT) diagram, 14, 16
- Continuous fields, noncontinuous vs., 1278–1279
- Continuous vibratory systems
  - of a bar, 1219
  - of a beam, 1219–1220
  - free-vibration solution, 1220–1222
    - normal-mode solution, 1220–1222
    - wave solution, 1220, 1221
  - of a shaft, 1219
  - of a string, 1217–1218
- Contradiction matrix, 622–624
- Contradictions, 616–618
- Control charts, 993–994
- Convection
  - forced, 816
  - free, 816
- Copper, 117
  - biostatic/antimicrobial properties of, 144–146
  - physical properties of, 118, 119, 121, 123, 147–148
  - pure, 118, 119, 121, 123, 147–148, 154
  - in stainless steel, 41
  - in steel, 22, 24
- Copper alloys, 117–219
  - biostatic/antimicrobial properties of, 144–146
  - casting, 199–201
  - compositions of, 118, 120–146
  - copper-nickel-zinc, 119
  - copper-silicon, 134
  - corrosion behavior of, 131, 137–140, 144, 195–196
    - dealloying/parting, 137, 138
    - erosion-corrosion/cavitation, 138, 196
    - forms of, 137–139, 196
    - galvanic/dissimilar-metal, 138, 139
    - health/environment, 139, 140, 144
    - stress--corrosion/cracking, 139
  - designations of, 118, 119
  - early history, 117–118
  - fabrication of, 146, 148, 154, 157, 194, 196–207
    - casting, 199–201
    - forging, 201, 202
    - machining, 146, 148, 154, 157, 196–203
    - welding/brazing/soldering, 202, 204–207
  - families of, 119
  - forging, 201, 202
  - machining, 146, 148, 154, 157, 196–203
    - boring, 194, 200
    - chip appearance and machinability, 146, 148, 196
    - drilling, 194, 200
    - free-cutting brass, 197, 198, 203
    - milling, 154, 157, 199
    - reaming, 194, 201
    - recommended practices, 148, 154, 157, 194, 196–203
    - sawing, 196, 197, 203
    - single-point turning tools, 148, 154, 197–199
    - threading/tapping, 196, 202
  - mechanical properties of, 127, 131, 154–194
    - C10100-C19200, 158–163
    - C23000-C28000, 163–165
    - C36000-C52700, 166–168
    - C61300-C69400, 169–171
    - C70600-C77000, 171–175
    - C81100-C89550, 176–182
    - C90300-C93800, 183–188
    - C95200-C96400, 189–193
    - temper designations, 155–157
  - physical properties of, 123, 144–146, 149–153
  - sleeve bearings, 214, 216, 217, 219
  - standards and specifications, 219
  - strengthening mechanisms for, 127, 128, 154
  - and temperature, 130, 131, 194
  - temper of, 128, 129, 155–157
  - tube/pipe products, 207–219
    - fuel gas distribution systems, 214
    - nonflammable medical gas piping systems, 212, 214
    - plumbing tube, 207–212
  - welding of, 202, 204–207
    - coppers and high-copper alloys, 202, 204
    - crack preventions, 206–107
    - dissimilar-metal combinations, 204, 205
    - distortion control, 206
    - filler metals, 206
    - safety and health, 207
    - shielding gas requirements, 205
    - welding processes, 205
    - weld properties, 207
- Corrosion
  - of aluminum alloys, 86–88
    - galvanic corrosion, 87–88
    - general corrosion, 86–87
    - pitting corrosion, 87
  - ceramic materials, 442–443
  - of copper and copper alloys, 131, 137–140, 144, 195–196
    - dealloying/parting, 137, 138
    - erosion-corrosion/cavitation, 138, 196
    - forms of, 137–139, 196
    - galvanic/dissimilar-metal, 138, 139
    - health/environment, 139, 140, 144
    - stress--corrosion/cracking, 139
  - dry, 268–269
  - as failure, 863, 913–920
    - biological corrosion, 919
    - cavitation, 919
    - crevice corrosion, 917
    - direct chemical attack, 914, 915
    - erosion corrosion, 918–919

- galvanic corrosion, 914–917
- hydrogen damage, 919
- intergranular corrosion, 918
- pitting corrosion, 917–918
- selective leaching, 918
- stress corrosion cracking, 920
- galvanic, 87–88
- hot-corrosion resistance, 329
- and magnesium and magnesium alloys, 284–285
- of nickel and nickel alloys, 267–273
  - dry corrosion, 268–269
  - nickel-copper alloys, 268
  - oxidation, 269
  - pitting attack, 269
  - wet corrosion, 268
- pitting corrosion, 87
- of stainless steels, 39–40, 43–47
  - crevice corrosion, 45–46
  - galvanic corrosion, 47
  - general corrosion, 43
  - intergranular corrosion, 46
  - pitting corrosion, 45
  - stress--corrosion cracking, 44–45
- superalloys:
  - hot-corrosion resistance, 329
  - postservice refurbishment/repair, 330–331
  - thermal barrier coatings, 329–330
- of titanium alloys, 222–223, 252–253
- wet, 268
- Cost-benefit analysis (materials selection), 482, 483
- Cost-per-unit-property method (materials selection), 470–471
- COVIRDS (Conceptual VIRtual Design System), 740, 741
- CP (cellulose proprionate), 351
- CPU, *see* Central Processing Unit
- CPU and I/O (Central Processing Unit and input/output) devices, 656–657
- Cracking
  - in copper alloys, 139
  - welding of copper alloys, 206–207
- Creep, 36, 48, 506–508, 893–898
  - defined, 496
  - in electronic packaging materials, 789–790
  - equations for calculating, 506–507
  - mechanism of, 506
  - prediction of long-term, 894–896
  - under uniaxial state of stress, 895–898
- Creep limit, 497
- Creep rupture, 960
- Creep strain, 959–960
- Creep stress, 499
- Crevice corrosion, 45–46, 917
- Critical crevice corrosion temperature (CCCT), 46
- Crystal lattice, 6, 7
- CSG (constructive solid geometry), 705–706
- CT (computed tomography), 1266–1267
- CT diagram, *see* Continuous-cooling transformation diagram

- Curved beams, 524–527
- Customer needs mapping, 993
- CyberGlove, 735–736
- CyberGrasp, 735–736
- CyberTouch, 735–736
- Cylinders, stresses on, 543–545

## D

- Damping capacity (hysteresis), 500
- Dargies's method (materials selection), 472–473
- Data, 450–464
  - for analytical comparisons, 452
  - for failure analysis, 455
  - for final design, 453
  - for maintenance, 455
  - for manufacturing, 454
  - for material specification, 453–454
  - for materials selection, 451–452
  - metadata, 456–457
  - for modeling material/product performance, 451
  - numeric databases as type of, 456
  - for preliminary design, 452–453
  - for quality assurance, 454–455
  - sources of, *see* data sources
  - textual, 456
- Databases, computerized materials, 485–486
- Data sources, 457–464
  - Alloy Center, 460–461
  - ASM International, 460–461
  - categories of, 457–458
  - Internet, 462–464
  - knovel.com, 462
  - platforms for, 459–460
  - quality/reliability of, 458–459
  - STN International, 461–462
- Dealloying ("parting"), 137, 138
- Decibels, 1231, 1234–1235
- Deformation
  - nickel alloys, 269, 271
  - of a solid, 558–560
- Degassing, 4, 24
- Delta iron, 6
- Deming wheel, 991–992
- Design
  - computer-aided, *see* Computer-aided design (CAD)
  - final, 453
  - for optimization, *see* Optimization
  - preliminary, 452–453
  - and TQM, 986–991
    - benchmarking, 988
    - guidelines, 990–991
    - Kume's approach, 989–990
    - plans for acquisition/process control, 989
    - process design review, 988–989
    - product design review, 986–987
    - quality design characteristics, 986

- quality function deployment (QFD), 987
- quality loss function, 987–988
- Six Sigma, 990
- steps for controlling design, 986
- Taguchi's approach, 989
- Design for Six Sigma (DFSS), 581–610
  - background of, 581
  - IDDOV process, 587–608
    - defining requirements, 589–591
    - developing the concept, 591–598
    - identifying the project, 588–589
    - optimizing the design, 597–608
    - verifying and launching, 607–608
  - management of, 584–587
  - myths about, 582
- DFX (Drawing Exchange Format), 713
- Diallyl phthalate, 375
- Die castings, mechanical properties of, 281, 282
- Diffusion, 6, 7
- Digital logic method (materials selection), 474–476
- Digitizers, 683–685
- Dilatometer, 14, 16
- Dimension-driven design, 651
- Dimensionless grouping, 1096–1097
- Direct chemical attack, 863, 914, 915
- Direct-search optimization methods, 838, 839–841
- Direct-view storage tube (DVST), 688
- Discontinuities, and stress, 500–501
- Discontinuous fiber-reinforced MMCs, 401
- Discrete components, 806, 807
- Discrete wiring, 810
- Dissimilar-metal combinations, 204, 205
- Distortion-Energy Theory (Hencky--Von Mises Theory), 504
- Distributed Virtual Workspace for Enhancing Communication (DIVERCITY), 753–754
- Double seals, 1182, 1183
- Double walls, 1245–1246
- Drawing Exchange Format (DFX), 713
- Drilling (copper alloys), 194, 200
- Driving simulation, 746–748
- Dry corrosion, 268–269
- Dual-phase steels, 31
- Ductile rupture, 863
- Ductility, 496, 788–789
- Duplex stainless steels, 34, 51, 57
- DVDs, 677–678
- DVST (direct-view storage tube), 688
- Dynamic analysis, 653, 654
- Dynamic fatigue measurements, 974, 975
- Dynamic response, 717
- Dynamic seals, 1174–1199
  - brush seals, 1192–1198
    - brush seal flow modeling, 1197
    - brush seal materials, 1197–1198
    - design considerations for, 1193–1195
    - leakage performance comparisons, 1195–1197

- emission concerns, 1180–1184
  - sealing approaches, 1181–1184
- honeycomb seals, 1191–1192
- initial seal selection, 1174–1177
- labyrinth seals, 1188–1191
  - applications of, 1190
  - and computer analysis tools, 1191
  - configurations of, 1188–1190
  - leakage flow modeling, 1188–1191
  - and rotordynamic stability, 1190, 1191
- mechanical face seals, 1176, 1178–1180
  - balance, 1176, 1178
  - leakage, 1178–1179
  - materials, 1179–1180
  - seal face flatness, 1179
  - noncontacting seals, 1183–1188

Dynamic stress, 499

## E

- EC inspection, *see* Eddy current inspection
- ECTFE (poly(ethylene chlorotrifluoroethylene)), 372
- Eddy current (EC) inspection, 1280–1285
  - impedance plane, 1281–1284
  - skin effect, 1281
- Elastic deformation, 863, 867–869
- Elasticity, 493
- Elastic limit, 494
- Elastohydrodynamic lubrication, 1084–1087, 1089–1147
  - contact stress/deformations, 1086, 1087, 1089–1096
    - elliptical contacts, 1086, 1087, 1089–1096
    - rectangular contacts, 1094, 1096
  - dimensionless grouping, 1096–1097
  - fluid film lubrication thickness, 1099–1104
  - hard-EHL results, 1097–1099
  - regimes, 1040
  - rolling-element bearings, 1102–1147
  - soft-EHL results, 1099
- Elastomers, 375–377, 801–802
- Elastorestrictive materials, 424
- Electrical contacts, 796
- Electrical steels, 29
- Electromagnetic shielding, 787
- Electronic displays, 686–688
- Electronic packaging, 782–818
  - component mounting, 806–808
    - discrete components, 806, 807
    - printed circuit board components, 807–808
  - concerns with, 782–783
  - design techniques for, 783–784
  - fastening/joining, 808–810
    - adhesives, 810
    - mechanical fastening, 808–809
    - welding/soldering, 809–810
  - interconnection, 810–811
    - board level, 810
    - discrete wiring, 810

- fiber-optic connections, 811
    - interequipment, 811
    - intermodule, 811
    - intramodule, 810
  - materials for, *see* electronic packaging materials
  - protective, 817–818
    - shipping environment, 817–818
    - storage equipment protection, 817
  - shock/vibration, 811–813
    - fragility, 811
    - shock, 811–812
    - testing, 812–813
    - vibration, 812
  - structural design, 813–815
    - complexity/mechanical impedance, 813–814
    - degree of enclosure, 814
    - stresses, 814–815
    - thermal expansion, 814–815
  - thermal design, 815–817
    - conduction, 815–816
    - evaporation, 817
    - forced convection, 816
    - free convection, 816
    - objectives, 815
    - radiation, 817
  - Electronic packaging materials, 784–806
    - applications, 791–798
      - electrical contacts, 796
      - encapsulation, 796–797
      - equipment attachment, 791–792
      - equipment/module enclosures, 792
      - equipment racks/frames/mounting structures, 792
      - finishes, 794–795
      - harsh-environment endurance, 797–798
      - mechanical joints, 793–794
      - position-sensitive assemblies, 795–796
      - temperature control, 792–793
    - candidate materials, 798–806
      - adhesives, 805–806
      - ceramics/glasses, 804–805
      - metals, 798–801
      - plastics/elastomers, 801–804
    - selection process, 784–791
      - chemical inertness, 785
      - combustability, 789
      - corrosion, 785–786
      - creep, 789–790
      - density, 787
      - ductility, 788–789
      - electrical conductivity, 784
      - electromagnetic and electrostatic shielding, 787
      - fatigue resistance, 788
      - hardness, 788
      - magnetic shielding properties, 787–788
      - moisture absorption, 790–791
      - strength, 787
      - sublimation, 789
      - temperature range, 786
      - thermal conductivity, 784
      - thermal emissivity, 784–785
      - thermal expansion, 785
      - wear resistance, 789
  - strength of, 787
  - thermal expansion of, 785
  - Electroplating
    - of aluminum alloys, 91
    - of magnesium and magnesium alloys, 285
  - Electrorheological materials, 424
  - Electrostatic shielding, 787
  - Electrostrictive materials, 422
  - Embrittlement, 22
  - Enameling steel, 29
  - Encapsulation, 796–797
  - Engineering thermoplastics, 351–365
    - polyamides (nylon), 355–360
    - polyarylates (PARs), 361, 362
    - polycarbonate/ABS alloys (PC/ABS), 360, 361
    - polycarbonates (PCs), 360
    - polyestercarbonates (PECs), 361, 362
    - polyphenylene ether (PPE), 362–364
    - thermoplastic polyesters, 352–355
  - Engineering workstations, 665–666
  - Envirobrasses, 141
  - Environmental failure, 931, 932
  - Environmentally enhanced fracture (brittle materials), 966–968
    - constant-loading-rate experiments, 967–968
    - inert strength for indented specimens, 968
  - Environmental stress, 774–775
    - heat stress, 774–775
    - vibration, 774–775
  - Epoxy resins, 373
  - Ergonomics, physical, *see* physical ergonomics
  - Erosion corrosion, 138, 196, 918–919
  - Esawi's and Ashby's method (materials selection), 473
  - Euler's formula, 537–538
  - Evaporation, 817
  - Experimental analysis, 654
  - Expert systems, 486–487
  - Exponential distribution (hazard rate model), 1002–1003
  - External memory, 671–678
  - External work, 499
  - Extreme-pressure lubricants, 1156–1157
- F
- Fabrication, *see* Manufacturing
  - Factor of safety, 498
  - Failure, 860–921, 925–932
    - analysis/restrospective design, 920–921
    - brinnelling, 863
    - brittle fracture, 863
    - ceramic, *see* Ceramic failure
    - chemical, 931, 932

corrosion, 863, 913–920
 

- biological corrosion, 919
- cavitation, 919
- crevice corrosion, 917
- direct chemical attack, 914, 915
- erosion corrosion, 918–919
- galvanic corrosion, 914–917
- hydrogen damage, 919
- intergranular corrosion, 918
- pitting corrosion, 917–918
- selective leaching, 918
- stress corrosion cracking, 920

 creep/stress rupture, 893–898
 

- prediction of long-term creep, 894–896
- under a uniaxial state of stress, 895–898

 criteria of, 860–861
 

- and design, 927–930
- direct chemical attack, 863
- ductile rupture, 863
- elastic deformation/yielding, 863, 867–869
- environmental, 931, 932

 fatigue, 875–893
 

- fatigue crack propagation, 888–893
  - loading/laboratory testing of, 876–880
  - nonzero mean stress, 883, 886–888
  - S-N-P* curves, 879–886

 fracture mechanics/unstable crack growth, 869–875
 

- fretting, 898–907
  - and material selection, 926–927
  - mechanical, 928
  - modes of, 508–510
  - and process, 927, 928, 930
  - and reliability, 1010–1011
  - and service conditions, 928, 931
  - thermal, 931
  - types of, 861–867
  - wear, 898, 907–913
  - yielding, 863

 Failure analysis, 931, 933–941
 

- brittle-coating method, 936
- chemical method, 936–937
- fractography, 939–940
- heat reversion, 937–938
- identification analysis, 933–934
- materials data for, 455
- mechanical testing, 938, 939
- microtoming, 938, 939
- nondestructive testing techniques (NDT), 939
- simulation testing, 941
- strain gauge method, 936
- stress analysis, 934–937
- thermal analysis, 939
- visual examination, 933

 Failure data and failure data collection sources, 1019–1020
 Failure Modes and Effect Analysis (FMEA), 697, 988, 1016–1017
 Failure rate allocation method, 1013
 Failure rate estimation models, 1018–1019
 

- for brake systems, 1018
- for compressor systems, 1019
- for filters, 1019
- for pumps, 1019

 Fatigue, 507–510, 863, 875–893
 

- fatigue crack propagation, 888–893
  - loading/laboratory testing of, 876–880
  - localized, 774
  - nonzero mean stress, 883, 886–888
  - resistance in electronic packaging materials, 788
  - S-N-P* curves, 879–886
  - whole-body, 773–774

 Fatigue crack propagation, 888–893
 Fatigue stress, 499
 Fault Tree Analysis (FTA), 1017
 FEA, *see* Finite-element analysis
 Feature-based modeling, 652–654
 FEM, *see* Finite-element method
 FEP (fluorinated ethylene--propylene), 371–372
 Ferrite, 9, 25
 Ferritic stainless steels, 3, 33–34, 49–50
 Fibers, as composite reinforcement, 387, 388
 Fiber-optic connections, 811
 Film-based radiography, 1263–1264
 Filters, failure rates for, 1019
 Final design, materials data for, 453
 Finishing
 

- aluminum alloys, 90–92
- magnesium alloys, 284–285

 Finite-element analysis (FEA), 652–653, 742–743
 Finite-element method (FEM), 557–580
 

- and deformation of solid, 558–560
- differential properties of shape functions, 570–572
- differentiation in referential coordinates, 572–575
- and equilibrium, 560–562
- FEM approximation, 567–568
- foundations of, 565–566
- global/local transformations, 569–570
- Hilbertian Sobolev spaces in, 566–567
- and infinitesimal linearly elastic constitutive laws, 562–565
- one-dimensional example of, 576–579
- processing, 575–576
- in three dimensions, 567

 Fishbone diagram, 992
 Fixed beam, 510
 Flexure, theory of, 511–520
 Floppy disks, 673
 Fluorinated ethylene--propylene (FEP), 371–372
 Fluorinated thermoplastics, 370–372
 

- fluorinated ethylene--propylene (FEP), 371–372
- poly(chlorotrifluoroethylene) (PCTFE), 371
- poly(ethylene chlorotrifluoroethylene) (ECTFE), 372
- poly(tetrafluoroethylene) (PTFE), 370, 371
- poly(vinyl fluoride) (PVF), 372

polyvinylidene fluoride (PVDF), 372  
FMEA, *see* Failure Modes and Effect Analysis  
Forced convection, 816  
Forced-harmonic vibration, 1211  
Forced nonharmonic vibration, 1211–1212  
Forced-vibration response, 1217  
Force field analysis, 993  
Forging  
  of copper alloys, 201, 202  
  of magnesium alloys, 284  
  of steel, 5  
  of superalloys, 322–323  
  of titanium alloys, 249–250  
FORTRAN, 698  
Fractography, 939–940  
Fracture, types of, 497  
Fracture mechanics, 869–875, 944–946  
Frames, 792  
Free convection, 816  
Free-cutting brass, 197, 198, 203  
Free-machining steels, 22  
Free-vibration, 1208–1211  
  normal-mode solution, 1220–1222  
  response, 1216–1217  
  wave solution, 1220, 1221  
Freeware, 691  
Frequency (of sound), 1231  
Frequency response, 717  
Fretting, 898–907  
Frit, 29  
FTA (Fault Tree Analysis), 1017  
Fuel gas distribution systems, 214  
  
G  
Galling failure, 866  
Galvanic corrosion, 914–917  
  of aluminum alloys, 87–88  
  copper alloys, 138, 139  
  in electronic packaging materials, 800  
  of stainless steels, 47  
Gamma iron, 6  
Gamma loop, 34  
Gap analysis, 995–996  
Gaskets, 1161–1168  
  metallic, 1165  
  nonmetallic, 1165  
  practical considerations for, 1166–1168  
  required bolt load, 1165  
Gas-lubricated bearings, 1068–1091  
  journal bearings, 1069–1084  
    herringbone groove, 1071, 1075, 1078–1084  
    pivoted pad, 1069–1077  
  thrust bearings, 1075–1091  
    Rayleigh step bearing, 1075–1078, 1085–1087  
    spiral-groove thrust bearings, 1078–1084, 1088–1091  
Gels, smart, 427–428

General distribution (hazard rate model), 1003  
Geological engineering, virtual reality applied to, 754–757  
Geometric dimensioning/tolerancing, STEP for, 727–728  
Gerber's Law, 508  
Glass fibers (as composite reinforcement), 388  
Global multiaxial fracture criterion (ceramics), 953  
Goal programming, 831–833  
Gold, 800–801  
Goodman's Law, 508, 887–888  
Gradient-based methods, 838–839  
Graphical user interface (GUI), 694–695  
Graphite fibers (as composite reinforcement), 388  
Grease (as lubricant), 1037–1038  
Guest Theory (Maximum-Shear Theory), 504  
GUI (graphical user interface), 694–695  
  
H  
Hadfield manganese steels, 20–21  
Hard-copy devices, 689–691  
Hard disks, 673  
Hard-EHL, 1097–1099  
Hardenability (of steel), 16–18  
Hardness, 496  
Hardware, 655  
  for CAD, 655–656  
  for virtual reality (VR), 734–738  
    input devices, 735–737  
    output devices, 736–738  
Harsh-environment endurance, 797–798  
Hazard rate models, 1002–1003  
  exponential distribution, 1002–1003  
  general distribution, 1003  
  normal distribution, 1003  
  Weibull distribution, 1003  
HDPE (high-density polyethylene), 339, 340  
Head hardening, 13  
Health issues, *see* Safety and health issues  
Heat-resistant steels, 35–36  
Heat reversion, 937–938  
Heat stress, 774–775  
Heat treatment  
  of nickel and nickel alloys, 272–276  
  of steel, 25–26  
Hencky--Von Mises Theory (Distortion-Energy Theory), 504  
Herringbone groove, 1071, 1075, 1078–1084  
High-copper alloys, 119  
  cast, 138  
  wrought, 124–129  
High-density polyethylene fibers (as composite reinforcement), 389–390  
High-density polyethylene (HDPE), 339, 340  
Higher alloy steels, 31–37  
  heat-resistant steels, 35–36  
  stainless steels, 31–35  
  tool steels, 35  
  ultrahigh-strength steel, 36–37

wear-resistant steels, 36

High-impact polystyrene (HIPS), 342, 343

High-leaded tin bronzes, 143

High-molybdenum alloys, 57

High-performance materials, 364–370

- aromatic polyketones (PEK, PEEK), 369, 370
- liquid crystalline polyesters (LCPs), 365–367
- polyamide imides (PAIs), 369
- polyarylsulfones (PSU, PES, PPSU), 365, 366
- polyetherimides (PEIs), 368–369
- polyimides (PMDA-ODA), 366–368
- polyphenylene sulfide (PPS), 364–365

High-performance steels, 31

High strength yellow bronzes, 140

Hilbertian Sobolev spaces, 566–567

HIPS (high-impact polystyrene), 342, 343

HoloSketch, 740

Honeycomb seals, 1191–1192

Hooke's law, 493

Horizontal shear, 512, 521

Hoshin planning method (TQM), 994–995

Hot-corrosion resistance, 329

Hot cracking, 54–56

Hot shortness, 20, 22

Human error, 1017–1018

Hybrid reliability allocation method, 1013–1014

Hybrid solid modeling, 651

Hydrodynamic lubrication, 1044–1061, 1068–1091

- gas-lubricated bearings, 1068–1091
- liquid-lubricated journal bearings, 1044–1051
- liquid-lubricated thrust bearings, 1050–1061
- regime, 1038–1040

Hydrogels, 427–428

Hydrogen

- in steel, 24
- in titanium alloys, 236

Hydrogen damage, 919

Hydrogen flakes, 24

Hydrostatic bearings, 1060–1069

- compensating elements of, 1066–1069
- pad coefficients, 1063–1066

Hypereutectoid steels, 9, 13

Hypoeutectoid steels, 9

Hysteresis (damping capacity), 500

**I**

IDDOV process, 587–608

- defining requirements, 589–591
- developing a concept, 591–598
- identifying the project, 588–589
- methodology, 582–584
- optimizing the design, 597–608
- verifying and launching, 607–608

Ideality, 615–617

Identification analysis, 933–934

IF (interstitial-free) steels, 3

IGES (Initial Graphics Exchange Specification), 712–713

Immersadesk, 750

Impact failure, 864–865

Impact polystyrene (IPS), 342, 343

Impact stress(es), 499, 527–530

Indented inert strength, 975

Inert strength for indented specimens, 968

Infinitesimal linearly elastic constitutive laws, 562–565

Infrared cameras, 1279–1280

Ingots

- melting/casting, 320
- steel, 5

Initial Graphics Exchange Specification (IGES), 712–713

Initial screening (materials selection), 469–473

- Ashby's method, 471–472
- cost-per-unit-property, 470–471
- Dargies's method, 472–473
- Esawi's and Ashby's method, 473
- limits on material properties, 470

Input devices, computer, 678–686

- digitizer, 683–685
- keyboard, 678–679
- light pen, 682–683
- mouse, 681–682
- scanner, 685–686
- touch pad, 679–680
- touch screen, 680–681
- trackball, 682
- TrackPoint, 682
- for virtual reality (VR), 735–737
  - CyberGlove, 735–736
  - CyberGrasp, 735–736
  - CyberTouch, 735–736
  - 6DOF mouse, 735
  - tracking devices, 735–736

Input/output device (I/O), 656–657

Integer programming (IP), 835, 837

Intergranular corrosion, 46, 918

Interleaved memory, 669–670

Internal memory, 670–671

Interstitial-free (IF) steels, 3

Inventiveness, Altshuller's theory of, *see* TRIZ (Theory of the Solution of Inventive Problems)

I/O (input/output) device, 656–657

IP, *see* Integer programming

IPS (impact polystyrene), 342, 343

Iron, 6, 799

Iron--carbon equilibrium diagram (steel), 6–13

Ironmaking, 4

Iron sulfide, 20

Isothermal transformation diagram (steel), 12–15

**J**

JDCAD, 740

Johnson's apparent elastic limit, 494

Joining

- electronic packaging, 808–810
  - adhesives, 810
  - mechanical fastening, 808–809
  - welding/soldering, 809–810
- magnesium and magnesium alloys, 283, 284
- plastics, 854, 856
- superalloys, 324, 325
- titanium alloys, 251–252
- Joint movements (ergonomics), 769–771
- Jominy test, 16
- Journal bearings
  - herringbone groove, 1071, 1075, 1078–1084
  - liquid-lubricated, 1044–1051
  - pivoted pad, 1069–1077

**K**

- Kaizen method (TQM), 992–993
- Keyboards, 678–679
- Kinematic analysis and synthesis, 653
- Knovel.com, 462
- Knowledge-based systems, 486–487
- K*-out-of-*m*-Unit network, 1007–1008
- Kume's approach (Process Improvement), 989–990

**L**

- Labyrinth seals, 1188–1191
  - applications of, 1190
  - and computer analysis tools, 1191
  - configurations of, 1188–1190
  - leakage flow modeling, 1188–1191
  - and rotordynamic stability, 1190, 1191
- Ladle, 4
- Lamellar, 9
- Lanthanum, 24
- LCPs (liquid crystalline polyesters), 365–367
- LDPE (low-density polyethylene), 339–340
- Lead, 24, 801
- Leaded brasses, 131
- Leaded coppers, 119, 145
- Leaded phosphor bronzes, 133
- Leaded red brasses, 138
- Leaded semired brasses, 139
- Leaded steels, 30
- Leaded tin bronzes, 142
- Light pens, 682–683
- Light-sensitive materials, 426
- Limestone, 4
- Linearization optimization methods, 841–842
- Linear low-density polyethylene (LLDPE), 339–341
- Linear programming, 835
- Linear static analysis, 716
- Liquid crystalline polyesters (LCPs), 365–367
- Liquid-lubricated journal bearings, 1044–1051
- Liquid-lubricated thrust bearings, 1050–1061
- Liquid penetrants, 1257
  - limitations of inspections of, 1259

- penetrant process, 1257, 1258
- reference standards, 1258
- LLDPE (linear low-density polyethylene), 339–341
- Localized fatigue, 774
- Local multiaxial fracture criterion (ceramics), 954–956
- Low-alloy steels, 29–31
- Low-density polyethylene (LDPE), 339–340
- Lubrication, 1024–1157
  - and bearing selection, 1032–1035
  - boundary, 1148–1157
    - effect of operating variables, 1154–1156
    - extreme-pressure lubricants, 1156–1157
    - film thickness, 1153–1155
    - formation of films, 1149–1152
    - physical properties of films, 1151–1153
  - on conformal/nonconformal surfaces, 1030–1032
  - elastohydrodynamic, 1084–1087, 1089–1147
    - contact stress/deformations, 1086, 1087, 1089–1096
    - dimensionless grouping, 1096–1097
    - film thickness, 1099–1104
    - hard-EHL results, 1097–1099
    - rolling-element bearings, 1102–1147
    - soft-EHL results, 1099
  - equations relevant to, 1041–1044
  - history of, 1024–1025
  - hydrodynamic and hydrostatic lubrication, 1044–1061, 1068–1091
    - gas-lubricated bearings, 1068–1091
    - liquid-lubricated journal bearings, 1044–1051
    - liquid-lubricated thrust bearings, 1050–1061
  - hydrostatic bearings, 1060–1069
  - materials for, 1035–1038
    - grease, 1037–1038
    - oil, 1036–1037
    - viscosity of, 1035–1036
  - regimes for, 1038–1041
    - boundary, 1040–1041
    - elastohydrodynamic, 1040
    - hydrodynamic, 1038–1040
  - symbols used with, 1025–1030

**M**

- Machining
  - of aluminum alloys:
    - multipoint tool operations, 89–90
    - single-point tool operations, 88–89
  - of copper alloys, 146, 148, 154, 157, 196–203
    - boring, 194, 200
    - chip appearance and machinability, 146, 148, 196
    - drilling, 194, 200
    - free-cutting brass, 197, 198, 203
    - milling, 154, 157, 199
    - reaming, 194, 201
    - recommended practices, 148, 154, 157, 194, 196–203
    - sawing, 196, 197, 203
    - single-point turning tools, 148, 154, 197–199

- threading/tapping, 196, 202
- of magnesium and magnesium alloys, 282
- of nickel and nickel alloys, 276

Magnesium, 278–280

- in electronic packaging materials, 800
- nonstructural applications of, 279
- structural applications of, 279–280

Magnesium alloys, 278–285

- corrosion/finishing of, 284–285
  - anodic coatings, 285
  - chemical conversion coatings, 284–285
  - electroplating, 285
  - painting, 285
- fabrication of, 282–284
  - forming, 284
  - joining, 283, 284
  - machining, 282
- properties of, 280–282
  - castings, 281, 282
  - physical, 282, 283
  - wrought materials, 281, 283
- recycling of, 285

Magnetic media, 671–675

Magnetic-particle inspection method, 1277–1279

- continuous vs. noncontinuous fields, 1278–1279
- demagnetizing the part, 1279
- inspection process, 1279
- magnetizing field, 1277–1278

Magnetic shielding, 787–788

Magnetic tape, 675–676

Magnetizing field, 1277–1278

Magneto-optical drives, 673–674

Magnetoresistive heads, 674–675

Magnetorheological materials, 424–425

Magnetostrictive materials, 423

Mainframe computers, 659, 661–662

Maintenance, materials data for, 455

Malleability, 496

Maltron ergonomic keyboard, 679

Manganese, 20, 22

Manganese bronze, 140

Manual material-handling systems, 776–777

Manufacturing

- ceramic materials, 446–448
- of composites, 385–386
- of copper alloys, 146, 148, 154, 157, 194, 196–207
  - casting, 199–201
  - forging, 201, 202
  - machining, 146, 148, 154, 157, 196–203
  - welding/brazing/soldering, 202, 204–207
- of magnesium alloys, 282–284
  - forming, 284
  - joining, 283, 284
  - machining, 282
- materials data for, 454
- of nickel alloys, 269, 271, 272, 274, 275
  - deformation, resistance to, 269, 271
  - strain hardening, 271, 272, 274, 275
- and virtual reality (VR), 748–752
  - assembly, 750–752
  - factory and process models, 749–751

Maraging steel, 36–37

Martensite, 13–15, 25

Martensitic stainless steel

- age-hardening, 50

Martensitic stainless steels, 34, 50

Materials data, *see* Data

Materials databases, 485–486

Materials selection, *see* Selection of materials

Matrix materials, 386, 390–393

- carbon, 393
- ceramic, 393
- metal, 393
- polymer, 390, 392–393
- properties of, 391

Maximum-Shear Theory (Guest), 504

Maximum-Strain Theory (Saint Venant), 504

Maximum-Stress Theory (Rankine's Theory), 504

MDPE (medium-density polyethylene), 339

Mechanical face seals, 1176, 1178–1180

- balance, 1176, 1178
- leakage, 1178–1179
- materials, 1179–1180
- seal face flatness, 1179

Mechanical failure, 928

Mechanical fastening, 808–809

Mechanical testing, 938, 939

Medical gas piping systems, nonflammable, 212, 214

Medium-density polyethylene (MDPE), 339

Melting

- superalloys, 316–321
  - AOD, 317–319
  - considerations, 320–321
  - remelted ingot processing, 320
  - VIM, 318–320
- titanium alloys, 247–249
  - cutting the cost, 248
  - defects/control, 248–249

Memory (computers), 667–678

- cache, 670–671
- external, 671–678
- interleaved, 669–670
- internal, 670–671
- nonvolatile, 668
- organizational methods, 669–670
- PROM, 669
- RAM, 668–669
- ROM, 669
- virtual, 671
- volatile, 668

Memory organizational methods, 669–670

Metadata, 456–457

- Metal matrix, 393
- Metal matrix composites (MMCs)
  - mechanical properties of, 400–402
    - discontinuous fiber-reinforced MMCs, 401
    - particle-reinforced MMCs, 401
  - physical properties of, 413–414
- Microalloyed steels, 30
- Microcomputers, 659, 662
- Microtoming, 938, 939
- Minicomputers, 659, 662
- Minimills, 4
- Minimum strength overload proof test, 965
- MINLP (mixed-integer nonlinear programming), 837
- Mish metal, 24
- Mixed-integer nonlinear programming (MINLP), 837
- MMCs, *see* Metal matrix composites
- Module enclosures, 792
- Modulus, section, 516, 519
- Modulus of elasticity, 497
  - defined, 495
  - superalloys:
    - cast superalloys, 310
    - wrought superalloys, 309–310
- Modulus of rupture, 516
- Mohr's Circle, 503
- Mohr's hypothesis, 953
- Molybdenum, 40–41, 44
  - in stainless steel, 40–41
  - in steel, 22
- Moment of inertia, 516, 531
- MOS RAM, 670
- Mounting structures, 792
- Mouse, 681–682, 735
- Mufflers, 1249–1250
- Multiaxial Weibull statistics, 953–956
  - global multiaxial fracture criterion, 953
  - local multiaxial criterion, 954–956
  - strength under compression loading, 953
- Multi-degree-of-freedom systems, 1215–1217
  - equations of motion, 1215–1216
  - forced-vibration response, 1217
  - free-vibration response, 1216–1217
- Multivariable unconstrained optimization methods, 838–839
- Muscle forces (ergonomics), 771–772
- Music wire, 37

N

- NASA Virtual Wind Tunnel, 743–744
- NDI, *see* Nondestructive inspection
- NDT (nondestructive testing techniques), 939
- Networks
  - computer, 662
  - reliability, 1003–1009
    - bridge network, 1009–1010
    - K*-out-of-*m*-Unit network, 1007–1008
    - parallel network, 1005
      - parallel-series network, 1006–1007
      - series network, 1004
      - series-parallel network, 1005, 1006
      - standby system, 1008–1009
- Neutron radiography, 1261–1263
- Nickel, 256–257
  - pure, 257
  - in stainless steel, 41
  - in steel, 22
- Nickel alloys, 256–277
  - and austenitic stainless steels, 51–53
  - classification of, 257–259
  - corrosion of, 267–273
    - nickel-copper alloys, 268
    - oxidation, 269
    - pitting attack, 269
  - fabrication of, 269, 271, 272, 274, 275
    - deformation, resistance to, 269, 271
    - strain hardening, 271, 272, 274, 275
  - heat treatment of, 272–276
    - prepared atmosphere, 275
    - reducing atmosphere, 274, 275
  - machining of, 276
  - mechanical properties of, 261
  - nickel alloys, 260
    - nickel-chromium-iron, 263–265
    - nickel-chromium-iron alloys, 263–265
    - nickel-chromium-molybdenum, 266–267
    - nickel-chromium-molybdenum alloys, 266–267
    - nickel-copper alloys, 260–263, 268
    - nickel-iron, 266
    - nickel-iron-chromium, 265–266
    - nickel-iron-chromium alloys, 265–266
  - rupture stress, 262
  - trademarks of, 277
  - welding of, 276
- Nickel-chromium-iron alloys, 263–265
- Nickel-chromium-molybdenum alloys, 266–267
- Nickel-copper alloys, 260–263, 268
- Nickel-iron, 266
- Nickel-iron-chromium alloys, 265–266
- Nickel-tin bronzes, 143
- Nitrogen
  - in steel, 24
  - in titanium alloys, 237
- Noise control, 601–602, 1239–1252
  - absorption, 1240–1242
  - mufflers, 1249–1250
  - recommendations for, 1250–1252
  - sound-isolation, 1242–1246
    - acoustic enclosures, 1244–1245
    - composite panel, 1243–1244
    - double walls, 1245–1246
    - transmission loss, 1242, 1243
  - vibration damping, 1247–1249
  - vibration isolation, 1246–1248

Nonconformal surfaces, 1030–1032  
 Noncontacting seals, 1183–1188  
 Noncontinuous fields, continuous vs., 1278–1279  
 Nondestructive flaw detection, 965–966  
 Nondestructive inspection (NDI), 1253–1303
 

- electronic references relating to, 1255
- future capabilities of, 1255–1256
- information sources for, 1254–1255
- instrumentation qualities in, 1254
- liquid penetrants in, 1257
- magnetic-particle, 1277–1279
  - continuous vs. noncontinuous fields, 1278–1279
  - demagnetizing the part, 1279
  - inspection process, 1279
  - magnetizing field, 1277–1278
- radiography, 1259–1267
  - attenuation of X-radiation, 1262, 1263
  - computed tomography, 1266–1267
  - film-based, 1263–1264
  - generations/absorptions of X-radiation, 1260, 1261
  - neutron radiography, 1261–1263
  - penetrameter, 1264–1265
  - real-time, 1265–1266
- thermal methods, 1279–1285
  - eddy current inspection, 1280–1285
  - infrared cameras, 1279–1280
  - probes/sensors, 1285–1286
  - thermal paints, 1280
  - thermal testing, 1280
- ultrasonic, 1267–1276, 1286–1303
  - bond-testing, 1276
  - inspection process, 1272–1276
  - properties of materials, 1286–1303
  - reflection/transmission of sound, 1269–1270
  - refraction of sound, 1270–1272
  - sound waves, 1268, 1269

Nondestructive testing techniques (NDT), 939  
 Nonflammable medical gas piping systems, 212, 214  
 Nonlinear static analysis, 716–717  
 Nonvolatile memory, 668  
 Nonzero mean stress, 883, 886–888  
 Normal distribution (hazard rate model), 1003  
 Normal-mode analysis, 716  
 Normal stress, 493  
 Numerical databases, 456  
 Numeric databases, 456  
 NURBS, 650–651  
 Nylons, *see* Polyamides

**O**  
 Oil (as lubricant), 1036–1037  
 Operating systems, 692–694  
 Opportunity analysis, 996  
 Optical data storage, 676–678  
 Optical mouse, 681–682  
 Optimization, 819–845
 

- applications of, 823–834
  - analysis/data reduction applications, 833–834
  - design applications, 824–830
  - operations/planning applications, 830–833
- constrained methods, 839–843
  - direct search, 839–841
  - linearization, 841–842
  - SQP (Successive Quadratic Programming), 843
  - transformation, 841
- requirements for application of, 820–822
- software, 843–844
- structure of problems, 834–837
- unconstrained methods, 838–839
  - multivariable, 838–839
  - single-variable, 838

O-rings, 1168–1170
 

- as basic sealing mechanism, 1168–1170
- material selection/chemical compatibility of, 1170
- preload/compression of, 1168–1170
- in rotary applications, 1170
- thermal effects on, 1170

Output devices, computer, 686–691
 

- electronic displays, 686–688
- hard-copy devices, 689–691
- for virtual reality (VR), 736–738

Oxidation
 

- of mickel alloys, 269

Oxygen
 

- in steelmaking, 4
- in titanium alloys, 237

**P**  
 PAs, *see* Polyamides  
 Packings/braided rope seals, 1170–1174  
 PAIs (polyamide imides), 369  
 PARs (polyarylates), 361, 362  
 Parallel network, 1005  
 Parallel-processing, 666–667  
 Parallel-series network, 1006–1007  
 Parametric modeling, 651  
 Parametric solutions, 614  
 Pareto diagram, 992  
 "Parting" (dealloying), 137, 138  
 Pascal, 698–699  
 PASCC, *see* Polythionic acid stress--corrosion cracking  
 Passivation, 43  
 Passive electronics, 442–444  
 Patenting, 37  
 PBT/PC alloy, 352–354  
 PBT (poly(butylene terephthalate)), 352, 353  
 PCs, *see* Personal computers; Polycarbonates  
 PC/ABS (polycarbonate/ABS) alloys, 360, 361  
 PCTFE (poly(chlorotrifluoroethylene)), 371  
 Pearlite, 9, 13, 20, 25  
 PECs (polyestercarbonates), 361, 362  
 PEEK (polyetheretherketone), 369, 370

PEIs (polyetherimides), 368–369  
 PEK (polyetherketone), 369, 370  
 Penetrometer, 1264–1265  
 PE (polyethylene), 339–341  
 Performance, modeling material/product, 451  
 Performance index (materials selection), 475–476  
 Personal computers (PCs), 664–665  
 PES (polyethersulfone), 365, 366  
 PET (poly(ethylene terephthalate)), 353, 354  
 Pet projects, 586  
 Phenolic resins, 373  
 Phosphor bronzes, 133  
 pH-sensitive materials, 426  
 Physical contradictions, 617, 618, 624–625  
 Physical ergonomics, 762–779  
   analysis in, 765–775  
     anthropometry, 765–767  
     biomechanics, 769–773  
     environmental stress, 774–775  
     localized fatigue, 774  
     range of motion, 767–768  
     strength, 768–769  
     whole-body fatigue, 773–774  
   basis of, 763–764  
   defined, 762  
   in design process, 764–765  
   disciplines contributing to, 764  
   example applications of, 775–779  
     manual material-handling systems, 776–777  
     refuse collection, 777–779  
   history of, 762–763  
 Piezoceramics, 444–445  
 Piezoelectric materials, 419–422  
 Pitch-catch inspection, 1272–1273  
 Pitting corrosion, 917–918  
   aluminum alloys, 87  
   nickel alloys, 269  
   stainless steel, 40, 41  
   stainless steels, 45  
 Pivoted pad, 1069–1077  
 Plastics, 335–377, 847–858  
   additives in, 337  
   chemical/solvent resistance of, 337  
   classification of, 336–337  
   elastomers, 375–377  
   for electronic packaging materials, 801–804  
   engineering thermoplastics, 351–365  
     polyamides (nylon), 355–360  
     polyarylates (PARs), 361, 362  
     polycarbonate/ABS alloys (PC/ABS), 360, 361  
     polycarbonates (PCs), 360  
     polyestercarbonates (PECs), 361, 362  
     polyphenylene ether (PPE), 362–364  
     thermoplastic polyesters, 352–355  
   fluorinated thermoplastics, 370–372  
     fluorinated ethylene--propylene (FEP), 371–372  
     poly(chlorotrifluoroethylene) (PCTFE), 371  
     poly(ethylene chlorotrifluoroethylene) (ECTFE), 372  
     poly(tetrafluoroethylene) (PTFE), 370, 371  
     poly(vinyl fluoride) (PVF), 372  
     polyvinylidene fluoride (PVDF), 372  
   functions of, 852–853  
   high-performance materials, 364–370  
     aromatic polyketones (PEK, PEEK), 369, 370  
     liquid crystalline polyesters (LCPs), 365–367  
     polyamide imides (PAIs), 369  
     polyarylsulfones (PSU, PES, PPSU), 365, 366  
     polyetherimides (PEIs), 368–369  
     polyimides (PMDA-ODA), 366–368  
     polyphenylene sulfide (PPS), 364–365  
   joining techniques, 854, 856  
   materials selection techniques, 853–856  
   part design, 854  
   part material selection strategy, 856, 857  
   and polymers, 847–852  
   polyolefinic thermoplastics, 339–342  
     polyethylenes, 339–341  
     polymethylpentane (PMP), 341, 342  
     polypropylene (PP), 340, 341  
   polyurethane/cellulosic resins, 350–351  
   properties of, 337–339  
   reinforced, 853  
   side-chain-substituted vinyl thermoplastics, 342–350  
     acrylonitrile/butadiene/styrene (ABS) polymers, 344, 345  
     acrylonitrile/styrene/acrylate (ASA) polymers, 345, 346  
     poly(methyl methacrylate) (PMMA), 346, 347  
     polystyrenes (PS, IPS, HIPS), 342–343  
     polyvinyl chloride (PVC), 348, 349  
     poly(vinylidene chloride) (PVDC), 349–340  
     styrene/acrylonitrile (SAN) copolymer, 343, 344  
     styrene/maleic anhydride (SMA) copolymer, 347  
     styrene/methyl methacrylate (SMMA) copolymer, 347, 348  
     syndiotactic polystyrene (SPS), 343, 344  
   thermosets, 372–375  
     alkyd resins, 374  
     amino resins, 375  
     diallyl phthalate, 375  
     epoxy resins, 373  
     phenolic resins, 373  
     unsaturated polyesters, 373–374  
     vinyl esters, 374  
 Plasticity, 493–494  
 Plates, stresses on, 545–549  
 Plate steels, 5  
 Plotters, 689–691  
 Plumbing tube, copper-alloy, 207–212  
 PMCs, *see* Polymer matrix composites  
 PMDA-ODA, 366–368  
 PMMA (poly(methyl methacrylate)), 346, 347  
 PMP (polymethylpentane), 341, 342  
 Poisson's ratio, 493

Poka-yoke method (TQM), 994  
 Polar moment of inertia, 531  
 Polymeric materials, *see* plastics  
 Polyacetals, 359–360  
 Polyamides (PAs, nylons), 355–360  
   acetals, 359–360  
   aromatic, 358, 359  
   PA 4/6, 357  
   PA 6 and PA 6/6, 355, 356  
   PA/PPE alloys, 356–357  
   semiaromatic polyamides, 357, 358  
 Polyamide imides (PAIs), 369  
 Polyarylates (PARs), 361, 362  
 Polyarylsulfones, 365, 366  
 Poly(butylene terephthalate) (PBT), 352, 353  
 Polycarbonates (PCs), 360  
 Polycarbonate/ABS alloys (PC/ABS), 360, 361  
 Poly(chlorotrifluoroethylene) (PCTFE), 371  
 Polyesters  
   thermoplastic, 352–355  
   unsaturated, 373–374  
 Polyestercarbonates (PECs), 361, 362  
 Polyetheretherketone (PEEK), 369, 370  
 Polyetherimides (PEIs), 368–369  
 Polyetherketone (PEK), 369, 370  
 Polyethersulfone (PES), 365, 366  
 Poly(ethylene chlorotrifluoroethylene) (ECTFE), 372  
 Polyethylene (PE), 339–341  
 Poly(ethylene terephthalate) (PET), 353, 354  
 Polyimides, 366–368  
 Polyketones, aromatic, 369, 370  
 Polymers, 847–852. *See also* Plastics  
   defined, 848  
   smart, 426–427  
   thermoplastic, 848  
 Polymerization reactions, 848  
 Polymer matrix, 390, 392–393  
 Polymer matrix composites (PMCs)  
   mechanical properties of, 396–400  
   physical properties of, 408, 409, 411, 412  
 Poly(methyl methacrylate) (PMMA), 346, 347  
 Polymethylpentane (PMP), 341, 342  
 Polymides, 366–368  
 Polyolefinic thermoplastics, 339–342  
   polyethylenes, 339–341  
   polymethylpentane (PMP), 341, 342  
   polypropylene (PP), 340, 341  
 Polyphenylene ether (PPE), 362–364  
 Polyphenylene sulfide (PPS), 364–365  
 Polyphenylsulfone (PPSU), 365, 366  
 Polypropylene (PP), 340, 341  
 Polystyrene (PS), 342–343  
 Polysulfone (PSU), 365, 366  
 Poly(tetrafluorethylene) (PTFE), 370, 371  
 Polythionic acid stress--corrosion cracking (PASCC), 44–45  
 Poly(trimethylene terephthalate) (PTT), 354, 355  
 Polyurethanes (PUs), 350  
 Polyurethane resins (PURs), 350  
 Polyvinyl chloride (PVC), 348, 349  
 Poly(vinyl fluoride) (PVF), 372  
 Poly(vinylidene chloride) (PVDC), 349–340  
 Polyvinylidene fluoride (PVDF), 372  
 Portable ultrasonic systems, 1275–1276  
 Position-sensitive assemblies, 795–796  
 Powder metallurgy  
   superalloys, 323–324  
   titanium alloys, 245–247  
 PPE, *see* Polyphenylene ether  
 PP (polypropylene), 340, 341  
 PPS, *see* Polyphenylene sulfide  
 PPSU, *see* Polyphenylsulfone  
 Precipitation hardening stainless steels, 35  
 Preliminary design, materials data for, 452–453  
 Printed circuit board components, 807–808  
 Probes/sensors, 1285–1286  
 Problem solving, algorithm for, *see* ARIZ  
 Process annealing, 25  
 Proeutectoid phase, 9  
 Programmable read-only memory (PROM), 669  
 PROM (programmable read-only memory), 669  
 Proportional limit, 494  
 Protective electronic packaging, 817–818  
   shipping environment, 817–818  
   storage equipment protection, 817  
 Prototyping  
   rapid, 720–722  
   virtual, 719–720  
 PS (polystyrene), 342–343  
 PSU, *see* Polysulfone  
 PTFE, *see* Poly(tetrafluorethylene)  
 PTT, *see* Poly(trimethylene terephthalate)  
 PUs (polyurethanes), 350  
 Pugh method, 482, 594–597  
 Pulse-echo inspection, 1272–1273  
 Pumps, failure rate estimation models for, 1019  
 PURs (polyurethane resins), 350  
 PVC (polyvinyl chloride), 348, 349  
 PVDC (poly(vinylidene chloride)), 349–340  
 PVDF (polyvinylidene fluoride), 372, 420–422  
 PVF (poly(vinyl fluoride)), 372

**Q**  
 QFD (quality function deployment), 987  
 Quality assurance  
   materials data for, 454–455  
   traditional approach to, 982  
 Quality function deployment (QFD), 987  
 Quantitative methods of materials selection, 466–487  
   case study, 476–481  
   comparing/ranking, 473–476  
   digital logic, 474–476  
   performance index, 475–476

- weighted-properties, 474–476
- computerization, 485–487
  - databases, 485–486
  - expert systems, 486–487
- initial screening, 469–473
  - Ashby's method, 471–472
  - cost-per-unit-property, 470–471
  - Dargies's method, 472–473
  - Esawi's and Ashby's method, 473
  - limits on material properties, 470
- optimum solution, 476
- requirements, 467–473
  - cost, 469
  - functional, 467
  - processability, 467, 469
  - reliability, 469
  - resistance to service conditions, 469
- substitution, 480, 482–484
  - case study, 484
  - cost-benefit analysis, 482, 483
  - Pugh method, 482
- and types of material information, 484–485
- Quenching, 25, 26
- QUEST, 750
- R
- Race conformity
  - of ball bearings, 1112, 1113
  - of roller bearings, 1117
- Racks, 792
- Radiation, 817
- Radiography (as nondestructive inspection method), 1259–1267
  - attenuation of X-radiation, 1262, 1263
  - computed tomography, 1266–1267
  - film-based, 1263–1264
  - generations/absorptions of X-radiation, 1260, 1261
  - neutron radiography, 1261–1263
  - penetrameter, 1264–1265
  - real-time, 1265–1266
  - RT (radiography testing), 1259
  - testing, 1259
- Radiography testing (RT), 1259
- Radius of gyration, 536–537
- RAM (random access memory), 668–670
- Random access memory, 668–670
- Range of motion (ROM), 767–768
- Rankine's Theory (Maximum-Stress Theory), 504
- Ranking, *see* Comparing/ranking
- Rapid prototyping, 720–722
- Raster plotters, 690–691
- Raster-scan terminals, 688
- Rayleigh step bearing, 1075–1078, 1085–1087
- Reaction injection molding (RIM), 350
- Read-only memory (ROM), 669
- Real-time radiography, 1265–1266
- Reaming (copper alloys), 194, 201

- Red brasses, 138
- Reduced instruction set computer (RISC), 663–664
- Refuse collection, 777–779
- Reinforced plastics, 853
- Reliability, 1000–1020
  - of brittle materials, 962–963
  - and design, 1011–1017
    - failure rate allocation method, 1013
    - FMEA (Failure Modes and Effect Analysis), 1016–1017
    - FTA (Fault Tree Analysis), 1017
    - hybrid reliability allocation method, 1013–1014
    - safety factor/safety margin, 1014–1015
    - stress-strength interference theory method, 1015–1016
  - and failure, 1010–1011
  - and failure data, 1019–1020
  - failure rate estimation models of, 1018–1019
    - brake system, 1018
    - compressor system, 1019
    - filter, 1019
    - pump, 1019
  - hazard rate models of, 1002–1003
    - exponential distribution, 1002–1003
    - general distribution, 1003
    - normal distribution, 1003
    - Weibull distribution, 1003
  - and human error, 1017–1018
  - networks of, 1003–1009
    - bridge network, 1009–1010
    - K*-out-of-*m*-Unit network, 1007–1008
    - parallel network, 1005
    - parallel-series network, 1006–1007
    - series network, 1004
    - series-parallel network, 1005, 1006
    - standby system, 1008–1009
    - statistical distributions of, 1001–1002
- Rephosphorized steels, 22
- Resilience, 499–501
- Resisting moment, 531
- Resisting shear, 512
- Resources, maximal use of, 617, 618
- Restrained beam, 510
- RIM (reaction injection molding), 350
- RISC (reduced instruction set computer), 663–664
- Roller bearings, 1107–1111, 1117–1120
  - crowning of, 1117
  - curvature sum and difference of, 1118–1120
  - free endplay and contact angle of, 1118, 1119
  - geometry of, 1107–1111
  - race conformity of, 1117
- Rolling-element, 1102–1147
  - ball bearings, 1103, 1106, 1108, 1109, 1112–1117
  - bearing types, 1102–1111
  - kinematics, 1120–1123
  - roller bearings, 1107–1111, 1117–1120
- Rolling-element bearings, 1102–1147
  - ball bearings, 1103, 1106, 1108, 1109, 1112–1117

- contact angle of, 1113–1115
- curvature sum and difference of, 1116–1117
- geometry of, 1112–1117
- race conformity of, 1112, 1113
- shoulder height of, 1115
- bearing types, 1102–1111
- kinematics, 1120–1123
- roller bearings, 1107–1111, 1117–1120
  - crowning of, 1117
  - curvature sum and difference of, 1118–1120
  - free endplay and contact angle of, 1118, 1119
  - geometry of, 1107–1111
  - race conformity of, 1117
- Rolling (steel), 5
- ROM, *see* Range of motion; Read-only memory
- RT (radiography testing), 1259
- Rupture
  - creep and stress, 893–898
  - modulus of, 516
  - work required for, 500
- Rupture strength, 495
- Rusting, 47

**S**

- Safety, factor of, 498
- Safety and health issues
  - copper and copper alloys, 139, 140, 144, 207
  - vibration, exposure to, 774–775
- Safety factor, 1014–1015
- Safety margin, 1014–1015
- SAN (styrene/acrylonitrile) copolymer, 343, 344
- Sant Venant Theory (Maximum-Strain Theory), 504
- Scanners, 685–686
- Scatter (ceramic failure), 948–952
  - of lifetime, 951–952
  - of strength, 948–952
- SCC (stress corrosion cracking), 920
- Seal(s), 1161–1199
  - double seals, 1182, 1183
  - dynamic, 1174–1199
    - brush seals, 1192–1198
    - emission concerns, 1180–1184
    - honeycomb seals, 1191–1192
    - initial seal selection, 1174–1177
    - labyrinth seals, 1188–1191
    - mechanical face seals, 1176, 1178–1180
    - noncontacting seals, 1183–1188
  - single seals, 1181–1182
  - static, 1161–1174
    - gaskets, 1161–1168
    - o-rings, 1168–1170
    - packings/braided rope seals, 1170–1174
  - tandem seals, 1182, 1183
- Secant formula, 538
- Section modulus, 516, 519
- Selection of materials
  - materials data for, 451–452
  - plastics, 853–856
  - quantitative methods, *see* Quantitative methods of materials selection
- Selective leaching, 918
- Selenium, 24
- Semiaromatic polyamides, 357, 358
- Semired brasses, 139
- Sensitization, 33
- Series network, 1004
- Series-parallel network, 1005, 1006
- SFMs, *see* Su-field models
- Shafts, torsional stresses in, 531–535
  - angle of twist, 532–533
  - formula for round shafts, 531–532
  - noncircular cross sections, 533
  - shearing stress, 532
  - ultimate strength, 533, 535
- Shape functions, differential properties of, 570–572
- Shape memory alloys, 428–429
- Shareware, 691
- Shear
  - deflection due to, 519–520
  - horizontal, 512, 521
  - resisting, 512
  - vertical, 512
- Shear diagrams, 512
- Shear strain, 493
- Shear stress, 492
- Shielding
  - electromagnetic, 787
  - electrostatic, 787
  - magnetic, 787–788
- Shipping environment protection, 817–818
- Shock
  - and electronic packaging, 811–812
  - isolation of, 1225–1226
  - spectrum of, 1212–1214
- Side-chain-substituted vinyl thermoplastics, 342–350
  - acrylonitrile/butadiene/styrene (ABS) polymers, 344, 345
  - acrylonitrile/styrene/acrylate (ASA) polymers, 345, 346
  - poly(methyl methacrylate) (PMMA), 346, 347
  - polystyrenes (PS, IPS, HIPS), 342–343
  - polyvinyl chloride (PVC), 348, 349
  - poly(vinylidene chloride) (PVDC), 349–340
  - styrene/acrylonitrile (SAN) copolymer, 343, 344
  - styrene/maleic anhydride (SMA) copolymer, 347
  - styrene/methyl methacrylate (SMMA) copolymer, 347, 348
  - syndiotactic polystyrene (SPS), 343, 344
- Silicon brasses, 134, 140
- Silicon bronzes, 134, 140
- Silicon-carbide based fibers (as composite reinforcement), 389
- Silver, 800–801
- Simple beam, 510
- Simple stress, 493
- Simulation testing, 941

Single-degree-of-freedom systems, 1207–1212  
   equation of motion, 1208  
   forced-harmonic vibration, 1211  
   forced nonharmonic vibration, 1211–1212  
   free vibration, 1208–1211  
 Single seals, 1181–1182  
 Single-variable unconstrained optimization methods, 838  
 6DOF mouse, 735  
 Six Sigma, 990. *See also* Design for Six Sigma  
 SKETCHPAD, 643–644  
 SLAM II, 750  
 Slenderness ratio, 537  
 Smart catalysts, 428  
 Smart materials, 418–431  
   catalysts, 428  
   elastorestrictive materials, 424  
   electrorheological materials, 424  
   electrostrictive materials, 422  
   future considerations for, 430–431  
   hydrogels, 427–428  
   light-sensitive materials, 426  
   magnetorheological materials, 424–425  
   magnetostrictive materials, 423  
   pH-sensitive materials, 426  
   piezoelectric materials, 419–422  
   polymers, 426–427  
   shape memory alloys, 428–429  
   thermoreponsive materials, 425  
   unusual behaviors of, 429  
   versatility of, 430  
 Smart polymers, 426–427  
 SMA (styrene/maleic anhydride) copolymer, 347  
 SMMA (styrene/methyl methacrylate) copolymer, 347, 348  
*S--N--P* curves, 879–886  
 Socket action, 550–551  
 Soderberg's Law, 508  
 Soft-EHL, 1099  
 Software, 691–701  
   for computer-aided design (CAD), 701–712  
     graphics software, 701–703  
     solid modeling, 703–712  
   for computer languages, 697–701  
   for GUI (graphical user interface), 694–695  
   for operating systems, 692–694  
   for optimization, 843–844  
   for virtual reality (VR), 738, 739  
   for X Window System, 695–697  
 Solaris, 693  
 Soldering, 202. *See also* Brazing  
 Solid, deformation of a, 558–560  
 Solid modeling, 651, 703–712  
   concatenation, 710  
   constructive solid geometry (CSG), 705–706  
   dimension-driven design, 651  
   feature-based, 652–654  
   parametric, 651  
   scaling, 711  
   transformations, 708–711  
     three-dimensional, 710–711  
     two-dimensional, 708–710  
   translation, 709–710  
   variational, 651  
 Solubility, 7  
 Solvent resistance (of plastics), 337  
 Sound, 1230–1252. *See also* Noise control  
   analyzers of, 1235  
   characteristics of, 1230  
   combined sources of, 1234  
   control of, *see* noise control  
   correction for background, 1236  
   decibels, 1231, 1234–1235  
   frequency/wavelength of, 1231  
   measurements of, 1236–1239  
   meters for, 1234  
   power/pressure of, 1231  
   ultrasonic:  
     reflection/transmission of, 1269–1270  
     refraction, 1270–1272  
   ultrasonic waves, 1268, 1269  
   velocity of, 1231–1233  
 Sound-level meter, 1235  
 Sound measurement, 1236–1239  
   of machines in semireverberant locations, 1237  
   of small machines in free field, 1236  
   two-surface method of, 1237–1239  
 Spalling failure, 866  
 Special copper alloys, 119  
 Spheres, stresses on, 543, 545  
 Spheroidizing, 25, 26  
 Spiral-groove thrust bearings, 1078–1084, 1088–1091  
 SPS (syndiotactic polystyrene), 343, 344  
 SQP (Successive Quadratic Programming), 843  
 Stainless steel(s), 31–35, 39–58  
   and AOD/dual certification/chemistry control, 47–49  
   austenitic, 19, 32–33  
   availability of, 49  
   chromium in, 40  
   copper in, 41  
   and corrosion, 39–40, 43–47  
     crevice corrosion, 45–46  
     galvanic corrosion, 47  
     general corrosion, 43  
     intergranular corrosion, 46  
     pitting corrosion, 45  
     stress--corrosion cracking, 44–45  
   duplex, 34, 51  
   effect of alloying elements on, 39–43  
   ferritic, 3, 33–34, 49–50  
   martensitic, 34, 50  
   molybdenum in, 40–41  
   nickel alloy, 51–53  
   nickel in, 41

- precipitation hardening, 35
- Web sites related to, 58
- welding of, 53–57
  - austenitic alloys, 55–56
  - carbon vs. stainless steel, 53–55
  - duplex stainless steels, 57
  - high-molybdenum alloys, 57
- Standard for the Exchange of Products (STEP), 713, 725–730
  - applications for, 725, 726
  - applications protocols for, 725–727
  - for CNC machining, 728–730
  - future of, 730
  - for geometric dimensioning/tolerancing, 727–728
- Standby system, 1008–1009
- Static analysis, 653
- Static seals, 1161–1174
  - gaskets, 1161–1168
    - metallic, 1165
    - nonmetallic, 1165
    - required bolt load, 1165
  - o-rings, 1168–1170
    - as basic sealing mechanism, 1168–1170
    - material selection/chemical compatibility of, 1170
    - preload/compression of, 1168–1170
    - in rotary applications, 1170
    - thermal effects on, 1170
  - packings/braided rope seals, 1170–1174
    - for high-temperature service, 1171–1174
- Statistical strength distribution, 964–965
- Steel(s), 3–37
  - alloy, *see* Alloy steel(s)
  - carbon, 27–29
  - classification/specifications, 26–27
  - development of properties of, 5–18
    - continuous-cooling transformation diagram, 14, 16
    - departure from equilibrium, 9, 12
    - hardenability concept, 16–18
    - iron–carbon equilibrium diagram, 6–13
  - electrical, 29
  - enameling, 29
  - free-machining, 22
  - heat treatment of, 25–26
    - full annealing, 25
    - normalizing, 25
    - quenching, 26
    - recrystallization annealing, 25
    - spheroidizing, 25, 26
    - stress relieving, 25
    - tempering, 26
  - hypereutectoid, 9, 13
  - hypoeutectoid, 9
  - lead, 30
  - manufacture of, 4–5
    - continuous casting, 4–5
    - ironmaking, 4
    - rolling/forging, 5
      - steelmaking, 4
      - maraging, 36–37
      - plate, 5
      - rephosphorized, 22
      - weathering, 22
- Steel columns, stresses on, 542–543
- Steelmaking, 4
- STEP, *see* Standard for the Exchange of Products
- Stereolithography, 721–722
- Stiffness, 496
- STN International, 461–462
- Storage environment protection, 817
- Strain, 493, 495
- Strain-Energy Theory, 504
- Strain gauge method, 936
- Strain hardening (nickel alloys), 271, 272, 274, 275
- Strand casting, 4–5
- Stratification method (TQM), 996
- Strength
  - breaking, 495
  - of brittle materials, 964–966
    - minimum strength overload proof test, 965
    - nondestructive flaw detection, 965–966
    - statistical strength distribution, 964–965
    - tests, 972–975
  - and ceramic failure, 945–947
    - minimum strength overload proof test, 965
    - nondestructive flaw detection, 965–966
  - in physical ergonomics, 768–769
  - rupture, 495
  - statistical strength distribution, 964–965
  - of titanium alloys, 222–223
  - ultimate, 494
  - yield, 494
- Stress(es), 491–555, 934–937
  - allowable unit, 498
  - axial, 493
  - on beams, 510–530
    - continuous beams, 522–525
    - curved beams, 524–527
      - and design, 520–523
    - flexure theory, 510–520
    - impact stresses, 527–530
    - vibratory stresses, steady/impulsive, 530
  - on columns, 536–543
    - steel columns, 542–543
    - theory, 537–539
    - wooden columns, 539–542
  - combined, 502–506
  - compressive, 492
  - concentration factors, 501
  - contact, 551, 552
  - creep, 499, 506–508
  - on cylinders/spheres, 543–545
    - thick walls, 544–545
    - thin walls, 543–544

- definitions, 492–499
- determination of principal, 502–503
- discontinuities, 500–501
- dynamic, 499
- in electronic packaging, 814–815
- fatigue, 499, 507–510
- impact, 499
- information sources about, 553–555
- nonzero mean, 883, 886–888
- normal, 493
- on plates, 545–549
- on rotating elements, 551, 553
- shafts/bending/torsion, 530–536
- shear, 492
- simple, 493
- socket action, 550–551
- static, 492–499
- tensile, 492
- torsional, 530–536
  - bending, 535–536
  - in shafts, 531–535
- total, 492
- true, 495
- on trunnions, 545, 549–550
- unit, 492
- and work/resilience, 499–501

Stress corrosion

- of copper and copper alloys, 139
- of stainless steels, 44–45

Stress corrosion cracking (SCC), 920

Stress rupture, 893–898

Stress-strain relationship, 494–496

Stress-strength interference theory method, 1015–1016

Styrene/acrylonitrile (SAN) copolymer, 343, 344

Styrene/maleic anhydride (SMA) copolymer, 347

Styrene/methyl methacrylate (SMMA) copolymer, 347, 348

Sublimation, 789

Successive Quadratic Programming (SQP), 843

Su-field models (SFM), 626–631

Superalloys, 287–334

- component production, 321–328
  - casting, 321–323
  - forging/powder metal, 322–324
  - information resources, 325, 327–328
  - joining, 324, 325
  - overview, 324–326
- compositions of:
  - cast superalloys, 296–297
  - wrought superalloys, 293–295
- corrosion and coatings, 328–330
  - hot-corrosion resistance, 329
  - postservice refurbishment/repair, 330–331
  - thermal barrier coatings, 329–330
- effect of temperature on:
  - cast superalloys, 300–301
  - wrought superalloys, 298–299, 302–304

- evolution of, 315–317
- for high-temperature applications, 332–333
- intermediate-temperature applications, 331–332
- manufacture of articles using, 289, 290
- melting/casting, 316–321
  - AOD, 317–319
  - considerations, 320–321
  - remelted ingot processing, 320
  - VIM, 318–320
- modulus of elasticity of:
  - cast superalloys, 310
  - wrought superalloys, 309–310
- obtaining information on, 290–292
- properties of, 307, 310, 311, 313–315
  - cast superalloys, 308
  - mechanical, 314–315
  - physical/environmental, 307, 310, 311, 313–314
  - wrought superalloys, 305–307
- strengthening of, 288–291

Supercomputers, 658–659, 661

Surface modeling, 650

Syndiotactic polystyrene (SPS), 343, 344

Systems evolution, laws of, 625–627

## T

Tandem mill, 5

Tandem seals, 1182, 1183

TBCs, *see* Thermal barrier coatings

Technical contradictions, 617

Temperature capability

- titanium alloys, 222

Temperature(s)

- ceramic failure at high, 958–961
- creep rupture, 960
- creep strain, 959–960
- and copper, 130, 131, 194
- effect of, on superalloys:
  - cast, 300–301
  - wrought, 298–299, 302–304

Tempered aluminum alloys, 68, 70

Tempering, 25

- copper alloys, 128, 129, 155–157
- steel, 26

Tensile strain, 493

Tensile stress (tension), 492

Teoriya Resheniya Izobretatelskikh Zadatch, *see* TRIZ

Tertiary phase diagrams, 6

Textual data, 456

Theory of the Solution of Inventive Problems, *see* TRIZ

Thermal analysis, 939

Thermal barrier coatings (TBCs), 329–330

Thermal expansion, 814–815

Thermal failure, 931

Thermal nondestructive inspection methods, 1279–1285

- eddy current inspection, 1280–1285
- infrared cameras, 1279–1280

- probes/sensors, 1285–1286
- thermal paints, 1280
- thermal testing, 1280
- Thermal paints, 1280
- Thermal shock, 957–958
- Thermal testing, 1280
- Thermoplastic polyesters, 352–355
  - PBT/PC alloy, 352–354
  - poly(butylene terephthalate) (PBT), 352, 353
  - poly(ethylene terephthalate) (PET), 353, 354
  - poly(trimethylene terephthalate) (PTT), 354, 355
- Thermoplastic polyurethanes (TPUs), 350
- Thermoplastics, 802–803
- Thermoresponsive materials, 425
- Thermosets, 372–375, 803–804
  - alkyd resins, 374
  - amino resins, 375
  - diallyl phthalate, 375
  - epoxy resins, 373
  - phenolic resins, 373
  - unsaturated polyesters, 373–374
  - vinyl esters, 374
- 3DM, 740
- 3-Draw, 739
- Thrust bearings
  - liquid-lubricated, 1050–1061
  - Rayleigh step bearing, 1075–1078, 1085–1087
  - spiral-groove thrust bearings, 1078–1084, 1088–1091
- Time–temperature transformation (TTT) diagrams, 12
- Tin
  - in electronic packaging materials, 801
  - in steel, 24
- Tin brasses, 132
- Tin bronzes, 142
- Tissue tolerances (ergonomics), 771–772
- Titanium alloys, 221–255
  - biomedical applications of, 253
  - corrosion, 252–253
  - cryogenic applications of, 253
  - high temperatures of, 226–229
  - information resources for, 255
  - manufacturing processes for, 246–252
    - casting, 250–251
    - forging, 249–250
    - joining, 251–252
    - residual stresses, 251
    - vacuum arc melting, 247–248
  - melting, 247–249
    - cutting the cost of, 248
    - defects/control, 248–249
  - metallurgy of, 225–226
  - microstructure/properties of, 229–247
    - alloy composition/general behavior, 229–232
    - alpha alloys, 237, 238
    - alpha-beta alloys, 238–239
    - beta alloys, 239
    - cast alloys, 240, 245
    - effects of alloy elements, 233, 234
    - elastic constants/physical properties, 233–235
    - hydrogen in, 236
    - intermetallic compounds/transient secondary phases, 233
    - mechanical properties, 237–247
    - oxygen/nitrogen in, 237
    - powder-formed alloys, 244, 245
    - processing effects, 234, 236
    - strengthening, 230, 233
      - wrought/cast/powder metallurgy products, 245–247
    - strength/corrosion capability of, 222–223
    - strengthening mechanisms for, 223, 224
    - temperature capability of, 222
- Tool steels, 35
- Torsional stresses, 530–536
  - bending, 535–536
  - defined, 530–531
  - in shafts, 531–535
    - angle of twist, 532–533
    - formula for round shafts, 531–532
    - noncircular cross sections, 533
    - shearing stress, 532
    - ultimate strength, 533, 535
- Total quality management (TQM), 980–996
  - approaches to, 984–985
    - Crosby's, 985
    - Deming's, 984–985
    - Juran's, 985
  - barriers to success, 984
  - in design phase, 986–991
    - benchmarking, 988
    - guidelines, 990–991
    - Kume's approach, 989–990
    - plans for acquisition/process control, 989
    - process design review, 988–989
    - product design review, 986–987
    - quality design characteristics, 986
    - quality function deployment (QFD), 987
    - quality loss function, 987–988
    - Six Sigma, 990
    - steps for controlling design, 986
    - Taguchi's approach, 989
  - elements of, 982, 983
  - methods of, 991–996
    - affinity diagram, 991
    - control charts, 993–994
    - customer needs mapping, 993
    - Deming wheel, 991–992
    - fishbone diagram, 992
    - force field analysis, 993
    - gap analysis, 995–996
    - Hoshin planning, 994–995
    - Kaizen, 992–993
    - opportunity analysis, 996
    - Pareto diagram, 992

- poka-yoke, 994
  - stratification, 996
- origins of, 980–981
- principles of, 983
- traditional quality assurance program, 982

Total strain, 493

Total stress, 492

Touch pad, 679–680

Touch screen, 680–681

Toughness, 496

TPUs (thermoplastic polyurethanes), 350

TQM (total quality management), 980–996

Trackball, 682

Tracking devices, 735–736

TrackPoint, 682

Tramp elements, 24

Transformations, 708–711

- optimization methods, 841
- three-dimensional, 710–711
- two-dimensional, 708–710

Transient response, 717

Translation, 709–710

Transmission loss, 1242, 1243

Transparent ceramics, 445, 446

Trip steels, 31

TRIZ (Theory of the Solution of Inventive Problems), 595, 596, 612–640

- ARIZ, 635–639
  - caution, 639
  - flowchart, 636
  - model of ideal solution step, 638–639
  - problem analysis step, 637
  - resource analysis step, 637–638
- class 4 standards, 630–635
  - group 4-1, 630, 631
  - group 4-2, 631, 632
  - group 4-3, 632–633
  - group 4-4, 633–634
  - group 4-5, 634–635
- and contradictions, 628–630
- definition of, 613
- foundational principles of, 615–618
  - contradictions, 616–618
  - ideality, 615–617
  - maximal use of resources, 617, 618
- origins of, 613–615
- scientific approach to, 618–622
- Su-field synthesis, 629–631
- tools of, 622–628
  - analytical tools, 626–628
  - contradiction matrix, 622–624
  - laws of systems evolution, 625–627
  - physical contradictions, 624–625
  - Su-field, 626–628

True discoveries, 614

True strain, 495

True stress, 495

True stress--strain relationship, 495–496

Trunnions, stresses on, 545, 549–550

TTT diagrams, *see* Time--temperature transformation diagrams

Tube/pipe products (copper and copper alloys), 207–219

- fuel gas distribution systems, 214
- nonflammable medical gas piping systems, 212, 214
- plumbing tube, 207–212

Tungsten, 23, 41

Tuyeres, 4

Twisting moment, 531

Two-surface method, 1237–1239

## U

UHMWPE (ultrahigh-molecular-weight polyethylene), 339

Ultimate strength, 494

Ultrahigh-molecular-weight polyethylene (UHMWPE), 339

Ultrahigh-strength steels, 36–37

Ultrasonic nondestructive inspection methods, 1267–1276, 1286–1303

- bond-testing, 1276
- inspection process, 1272–1276
  - portable ultrasonic systems, 1275–1276
  - pulse-echo/pitch-catch inspection, 1272–1273
  - transmission vs. pulse echo, 1273–1275
- properties of materials, 1286–1303
- reflection/transmission of sound, 1269–1270
- refraction of sound, 1270–1272
- sound waves, 1268, 1269

Unconstrained methods for optimization, 838–839

- multivariable, 838–839
- single-variable, 838

Unified Numbering System (UNS), 26

Unit strain, 493

Unit stress, 492, 498

UNIX, 692–693

Unsaturated polyesters, 373–374

UNS (Unified Numbering System), 26

## V

Vacuum arc melting, 247–248

Vacuum induction melting (VIM), 318–320

VADE (Virtual Assembly Design Environment), 751

Variational modeling, 651

Vector plotters, 689–690

Vector refresh terminals, 686–688

Vertical shear, 512

Very low-density polyethylene (VLDPE), 339

Vibration(s), 1204–1212, 1215–1228. *See also* Shock

- adverse health outcomes from, 774–775
- of beams, 530
- of continuous vibratory systems, 1217–1222
- damping, 1247–1249
- and dynamics study, 1204
- and electronic packaging, 811–813
- isolation of, 1222–1226, 1246–1248

- modeling of, 1205–1207
- in multi-degree-of-freedom systems, 1215–1217
  - equations of motion, 1215–1216
  - forced-vibration response, 1217
  - free-vibration response, 1216–1217
- in single-degree-of-freedom systems, 1207–1212
  - equation of motion, 1208
  - forced-harmonic vibration, 1211
  - forced nonharmonic vibration, 1211–1212
  - free vibration, 1208–1211
- sources of, 1204
- standards for, 1226–1227
- study of, 1205
- symbols used with, 1227–1228
- VIM, *see* Vacuum induction melting
- Vinyl esters, 374
- Vinyl thermoplastics, side-chain substituted, *see* Side-chain-substituted vinyl thermoplastics
- VIRCON, 753
- Virtual Assembly Design Environment (VADE), 751
- Virtual memory, 671
- Virtual prototyping, 719–720
- Virtual Reality Laboratory, 756
- Virtual reality (VR), 732–757. *See also* Computer-aided design (CAD)
  - in civil engineering/construction, 752–755
    - DIVERCITY, 753–754
    - VIRCON, 753
  - in concept design, 739–742
    - 3DM, 740
    - 3-Draw, 739
    - COVIRDS, 740, 741
    - HoloSketch, 740
    - JDCAD, 740
    - virtual sculpting, 741–742
  - in data visualization, 742–746
    - CFD, 743–746. *See also* Computational Fluid Dynamics (CFD)
    - FEA (Finite-Element Analysis), 742–743
  - defined, 732–733
  - in driving simulation, 746–748
  - in geology/chemical engineering, 754–757
  - hardware for, 734–738
    - input devices, 735–737
    - output devices, 736–738
  - in manufacturing, 748–752
    - assembly, 750–752
    - factory and process models, 749–751
  - software for, 738, 739
  - types of, 733–734
- Virtual sculpting, 741–742
- ViSTA FlowLib, 744–746
- Visual examination, 933
- VLDPE (very low-density polyethylene), 339
- Volatile memory, 668
- VR, *see* Virtual reality
- VR-CFD, 744–745
- VR-Fact!, 749–750
- VRFactory, 750
- W
- Wear, 789, 898, 907–913
- Wear-resistant steels, 36
- Weathering steels, 22
- Weibull distribution (hazard rate model), 1003
- Weibull statistics, 953–956
  - compression loading, 953
  - global multiaxial fracture criterion, 953
  - local multiaxial fracture criterion, 954–956
- Weibull tests, 970–972
- Weighted-properties method (materials selection), 474–476
- Welding. *See also* Brazing; Soldering
  - beam, design of welded, 827–830
  - carbon vs. stainless steel, 53–55
  - of copper and copper alloys, 202, 204–207
    - coppers and high-copper alloys, 202, 204
  - crack prevention, 206–207
  - dissimilar-metal combinations, 204, 205
  - distortion control, 206
  - filler metals, 206
  - safety and health, 207
  - shielding gas requirements, 205
  - welding processes, 205
  - weld properties, 207
  - nickel and nickel alloys, 276
  - of stainless steels, 53–57
    - austenitic alloys, 55–56
    - carbon vs. stainless steel, 53–55
    - duplex stainless steels, 57
    - high-molybdenum alloys, 57
- Welding/soldering, 809–810
- Wet corrosion, 268
- Whole-body fatigue, 773–774
- Windows NT, 693–694
- Wire, music, 37
- Wireframe modeling, 649
- Wireless mouse, 681
- WITNESS VR, 750
- Wooden columns, stresses on, 539–542
- Word length, 662
- Work, 499–501
- Workstations, 665–666
- Wrought alloys
  - aluminum, 92–107
  - copper, 124–129, 131–136
  - titanium, 245–247
- Wrought superalloys
  - compositions of, 293–295
  - dynamic moduli of elasticity for, 309–310
  - effect of temperature on, 298–299, 302–304
  - physical properties of, 305–307

## X

### X-radiation

attenuation of, 1262, 1263

generations/absorptions of, 1260, 1261

X Window System, 695–697

## Y

Yellow brasses, 139

Yielding failure, 863, 867–869

Yield point, 494

Yield strength, 494